

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HUB3 1" STL Ins Conduit Hub *Crouse-Hinds*

Catalog Number	HUB3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Hub Conduit Hub, Malleable Iron, 1",
	Space-Saver
Weight per unit	0.4700 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Male Threaded, Tapered Female Threaded
dimensions	1.7800 IN X 1.7800 IN X 1.5700 IN
Matorial	Malloable Iron

Material, Color, and Finish

Finish	Zinc Electroplated
--------	--------------------

Dimensions and Weight

Size	1	İ	n
- X.i X			

Descriptions

Description	1" STL INS CONDUIT HUB
extra long description	CRS-H HUB3 1 COND HUB CAST IRON
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series HUB conduit hub, Malleable iron, 1", Space-Saver
Product Type	1 Cond Hub Cast Iron
Special Features	1-7/8 In Diameter X 1-3/8 In Length, Weight 50 Lb per 100

Manufacturer Information

Brand	Eaton
GTIN	00782274490373
Manufacturers Part Number	HUB3
UPC	782274490373

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS
	AND THREADLESS CONNECTOR
Type	Conduit hub



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Carton	5
Weight Per each	0.47

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
Enclosure	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2
standard	UL 514B, CUL, CSA C22.2