



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



IM222503N 22-18 Fully Insulatd Male Disconnect

Nsi Industries

| | |
|------------------|---|
| Catalog Number | IM222503N |
| Manufacturer | Nsi Industries |
| Description | 22-18 Awg Fully Insulatd Male Disconnect, 50/Pack |
| Weight per unit | 0.1800 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|---------------------|------------------|
| Material | Nylon Insulation |
| Number of Terminals | 1 |
| Terminal Size | .250 x .032 |
| Voltage Rating | 600 V |
| Wire Size | 22-18 AWG |

Material, Color, and Finish

| | |
|-------|-----|
| Color | Red |
|-------|-----|

Descriptions

| | |
|------------------------|---|
| Description | 22-18 FULLY INSULATD MALE DISCONNECT |
| extra long description | NSI IM22-250-3N 22-18 FULLy InsULat |
| Features | 22-18 AWG FULLy InsULatd Male Disconnect, 50/Pack |
| Long Description | 22-18 AWG FULLy InsULatd Male Disconnect, 50/Pack |
| Product Type | 22-18 Fully Insulatd Male |
| Special Features | Nylon Fully Insulated Male Disconnect 22-18 AWG - 50 Pack |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00662381069290 |
| Manufacturers Part Number | IM22-250-3N |
| UPC | 662381069290 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---------------------------------------|
| Category Description | TERMINALS |
| Type | Nylon Fully Insulated Male Disconnect |

Availability

| | |
|-------------|----|
| minimum qty | 50 |
|-------------|----|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 50 |
| Weight Per each | 0.18 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

| | |
|--------------------------|------------------|
| Application | Wire Termination |
| environmental conditions | 105 C |
| standard | cULus |