

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLD7503 750-250 2S 3 Multi Cable Insul Tap Nsi Industries

Catalog Number	IPLD7503
Manufacturer	Nsi Industries
Description	The Polaris IPLD750-3 Multi-Tap Dual-Sided Entry Connector Features 3 Ports Sized For 750 - 250 MCM Wires. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applications, Including Installation In Cable Trays,
Weight per unit	
Product Category	Large Terminals & Connectors
eatures	
Material	Aluminum
Number of Conductors	3
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR
Wire Size	750-250 MCM
Wire Type	
Naterial, Color, and Finish	
Color	Black
Finish	Plastisol Insulated
imensions and Weight	
Size	L=4.950 - W=3.410 - H=3.420



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	750-250 2S 3 MULTI CABLE INSUL TAP
extra long description	NSI IPLD750-3 POLARIS Ins Multi-Tap
Features	The Polaris IPLD750-3 3-Port Dual-Sided Connector provides the
	simplest solution for forming a secure connection between up to
	three conductors in applications including cable trays, panel
	boards, ducts, raceways or troughs. Sized for 750 - 250 MCM
	wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than
	traditional uninsulated connector options using just a hex key
	and torque wrench. The aluminum alloy body is wrapped in
	high-dielectric stren
Long Description	The Polaris IPLD750-3 Multi-Tap Dual-Sided Entry Connector
	features 3 ports sized for 750 - 250 MCM wires. The body is made
	from aluminum alloy wrapped in a layer of plastisol insulation.
	Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the
	connections. Installs with a hex key and torque wrench, without
	any tape or additional supplies. Designed for use in a wide range
	of splicing applications, including installation in cable trays,
Product Type	Polaris Ins Multi-Tap 750 3 Port Dse
Special Features	(3) 750-250 MCM - Dual Rated
Manufacturer Information	
Brand	Polaris
GTIN	00662381926012
Manufacturers Part Number	IPLD750-3
UPC	662381926012
Taxonomies, Classifications, and Cate	•
Category Description	SPLIT BOLTS
Туре	Double Sided Entry
Packaging	
Carton	3
Weight Per each	1.3999
Uses, Certifications, and Standards	
Application	Wire Termination
environmental conditions	90 C
standard Tomporature Pating	
Temperature Rating	90 C