

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ITCSN11009BULK Heat Shrink Heavy-Wall Cable Sleeve, Black, 9" Minnesota Mining (3M)

Catalog Number	ITCSN11009BULK
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Cable Sleeve Itcsn Is A Heavy Wall Sleeve That
	Provides Abrasion, Corrosion and Chemical Resistance. This Sleeve Has A 3:1 Shrink Ratio to Offer Electrical Insulation For 1
	KV Rated Applications. It Features A Cross Linked Polyolefin
	Construction That Provides Moisture Seal Protection.
Weight per unit	0.0961 (lbs/each)
Product Category	Insulating Materials
Descriptions	
Description	HEAT SHRINK HEAVY-WALL CABLE SLEEVE,BLACK,9"
extra long description	3M 7000132157 3M™ Heat Shrink Heavy
Features	3M™ Heat Shrink Cable Sleeve ITCSN is a split resistant sleeve with a factory applied adhesive/sealant that offers reliable performance for electrical splices, connections and terminations.
	It is perfect for insulating secondary splices, direct buried, submersible or dig in repairs, as well as physical protection of high voltage, air insulated connectors or lugs. It withstands temperatures of 67 to 230 degrees F (55 to 110 degrees C). UL
	Listed, CSA Certified and RoHS 2011/65/EU Compliant.
Long Description	3M™ Heat Shrink Cable Sleeve ITCSN is a heavy wall sleeve that provides abrasion, corrosion and chemical resistance. This sleeve has a 3:1 shrink ratio to offer electrical insulation for 1 kV rated applications. It features a cross linked polyolefin construction that provides moisture seal protection.
Product Type	3M [™] Heat Shrink Heavy-Wall Cable Sleeves Itcsn
Manufacturer Information	
Brand	3M
GTIN	00054007089704
Manufacturers Part Number	IT1.100BK9"L
UPC	054007089704
Taxonomies, Classifications, and Categorian	
Category Description	HEAT/COLD SHRINK
Туре	Heavy Wall
Packaging	
Carton	100
Weight Per each	0.0961

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards	
standard	UL, CSA