

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## ITH750 750MCM-1/0AWG 2PRT BLK HD Multi-Tap Conn Nsi Industries

| Catalog Number              | ITH750  |  |
|-----------------------------|---|--|
| Manufacturer                | Nsi Industries  |  |
| Description                 | The Polaris Ith-750 Multi-Tap Dual-Sided Entry Connector Features 2 Ports Sized For 750 MCM - 1/0 Awg Wires. The Heavy-Duty Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Each Port Has Two Pressure Screws to Ensure The Best Connection Possible In Demanding Applications. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additi |  |
| Weight per unit             | 1.8 (lbs/each)  |  |
| Product Category            | Large Terminals & Connectors  |  |
| Features                    |   |  |
| Material                    | Aluminum  |  |
| Number of Conductors        | 2   |  |
| Poles                       | 1   |  |
| Voltage Rating              | 600 V   |  |
| Warranty                    | 1 YEAR  |  |
| Wire Size                   | 750-250 MCM   |  |
| Wire Type                   | Class B & C   |  |
| Material, Color, and Finish |   |  |
| Color                       | Black   |  |
| Finish                      | Plastisol Insulated   |  |
| Dimensions and Weight       |   |  |
| Size                        | L=3.480 - W=4.500 - H=3.500   |  |



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| _     | •   |      |    |
|-------|-----|------|----|
| 11000 | rin | TIAR | •  |
| Desc  |     |      | 17 |
| -     |     |      | •  |

standard

Temperature Rating

| Descriptions                       |   |  |  |
|------------------------------------|---|--|--|
| Description                        | 750MCM-1/0AWG 2PRT BLK HD MULTI-TAP CONN  |  |  |
| extra long description             | NSI ITH-750 POLARIS Ins HD 2 Port 7   |  |  |
| Features                           | The Polaris ITH-750 2-Port Dual-Sided Heavy-Duty Connector provides the simplest solution for forming a secure connection between two conductors in challenging applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 750 MCM - 1/0 AWG wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The aluminum alloy body is wrapped in high |  |  |
| Long Description                   | The Polaris ITH-750 Multi-Tap Dual-Sided Entry Connector features 2 ports sized for 750 MCM - 1/0 AWG wires. The heavy-duty body is made from aluminum alloy wrapped in a layer of plastisol insulation. Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the connections. Each port has two pressure screws to ensure the best connection possible in demanding applications. Installs with a hex key and torque wrench, without any tape or additi |  |  |
| Product Type                       | Dolaris Inc UD 2 Dort 750   |  |  |
| Special Features                   | (2) 750-250 MCM - Dual Rated  |  |  |
| Manufacturer Information           |   |  |  |
| Brand                              | Polaris   |  |  |
| GTIN                               | 00662381926401  |  |  |
| Manufacturers Part Number          | ITH-750   |  |  |
| UPC                                | 662381926401  |  |  |
| Faxonomies, Classifications, and ( | Categories  |  |  |
| Category Description               | TERMINAL BLOCKS POWER DIST BLOCKS   |  |  |
| Туре                               | Multi Cable   |  |  |
| Packaging                          |   |  |  |
| Carton                             | 3   |  |  |
| Weight Per each                    | 1.75  |  |  |
| Jses, Certifications, and Standard |   |  |  |
| Application                        | Wire Termination  |  |  |
| environmental conditions           | 90 C  |  |  |
|                                    | LII 4044/D  |  |  |

90 C

UL 486A/B