

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



JDL4 4A 600V Class J Time Delay Fuse Edison Fuses

•	
Catalog Number	JDL4
Manufacturer	Edison Fuses
Description	Eaton Edison Series JDL Fuse, Time-Delay Current-Limiting Fuse, Non-Indicating, 4 A, Class J, Non-Indicating, 200 Kaic, Standard, 10, 600 V
Weight per unit	0.0010 (lbs/each)
Product Category	Dual Element
atures	
amperage rating	4 A

Feat

amperage rating	4 A
amps	4
class	Class J
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
Fuse Type	Class J Time Delay Fuses
interrupt rating	200 kAIC
Voltage	600V
Voltage Rating	600 V

Descriptions

Description	4A 600V CLASS J TIME DELAY FUSE
extra long description	MOR T626-JDL4 JDL4 Time Delay 600V/
Features	Edison's UL Class J fuse products are offered in both Dual-Element Time-Delay (JDL) and Fast-Acting (JFL) types. Both types have 200,000 amp interrupting rating at 600Vac RMS Sym amps. Their small physical size and high performance characteristics makes Class J fuses ideal for any space-limited applications. Edison's JFL fuses are best suited for the protection of non-inductive loads such as resistive heating and lighting circuits.
Long Description	Eaton Edison series JDL fuse, Time-delay current-limiting fuse, Non-indicating, 4 A, Class J, Non-indicating, 200 kAIC, Standard, 10, 600 V
Product Type	JDL4 Time Delay 600V/4a
Special Features	Non-Indicating Non-Indicating
nufacturer Information	

Manufacturer Information

Brand	Eaton
GTIN	00782634249153
Manufacturers Part Number	JDL4
UPC	782634249153



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	Fuses & Fuse Accessories	
Туре	FUSE	
Packaging		
Carton	1	
Package	10	
Weight Per each	0.001	
Uses, Certifications, and Standards		
Application	Datacenters - Facilities: Critical Power	

CSA Certified, UL Listed, RoHS Compliant, CE Marked