

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## JJS6 6A 600V Vfa Class T Fuse Bussmann Fuses

Catalog Number	JJS6
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series JJS Fuse, Current-Limiting Very Fast Acting Fuse, Small Footprint, VFD Line Protection, 6 A, Class T, Non-Indicating, Ferrule End X Ferrule End, 200 Kaic At 600 V, Standard, 10, 600 V
Weight per unit	0.0400 (lbs/each)
Product Category	Renewable & Non-Renewable
Features	
amperage rating	6
connection	Ferrule End X Ferrule End
dimensions	0.5600 IN X 0.5600 IN X 1.5000 IN
Fuse Class	Class T
interrupt rating	200 kAIC at 600 Vac
media	Yes
Voltage Rating	600 V
Dimensions and Weight	
Size	0.56 In Diameter X 1.50 In Length
Descriptions	
Description	6A 600V VFA CLASS T FUSE
extra long description	BUSS JJS-6 TRON FAST ACTING FUSE CL
Features	Bussmann's Class T current-limiting, fast-acting fuses. Provides 10X better current limitation to help prevent equipment damage caused by short-circuit events. 200 kA Interrupting rating complies with NEC Section 110.9 for today's large capacity systems. Small, space-saving fuses provide a high degree of current limitation on short-circuits for excellent component protection.
Long Description	Eaton Bussmann series JJS fuse, Current-limiting very fast acting fuse, Small footprint, VFD line protection, 6 A, Class T, Non-indicating, Ferrule end x ferrule end, 200 kAIC at 600 V, Standard, 10, 600 V
Product Type	<del>ç</del>
Special Features	Small Footprint



## **E**LLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Eaton
GTIN	00051712628068
Manufacturers Part Number	JJS-6
UPC	051712628068
Taxonomies, Classifications, and Ca	tegories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.04
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	UL Listed ,CSA Certified,CE Marked,RoHS Compliant