Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



K1259 1-1/4 90D Liq-Tite Conn

Hubbell Incorporated Delaware

Catalog Number	K1259
Manufacturer	Hubbell Incorporated Delaware
Description	1 1/4" 90° Liquidtight Connector Non-Insulated
Weight per unit	9.3 (lbs/each)
Product Category	Liquid Tight Fittings

Features

insulation	False
Insulation Type	Non-Insulated
Material	Steel

Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

Dimensions and Weight

Length	2-9/16
Width	2-1/16

Descriptions

Description	1-1/4 90D LIQ-TITE CONN
extra long description	KIL K1259 1 1/4" 90° LT CONNECTOR N
Long Description	1 1/4" 90° Liquidtight Connector Non-Insulated
Product Type	1 1/4" 90° LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

Manufacturer Information

Brand	KILLARK
GTIN	00783936998572
Manufacturers Part Number	K1259
series	K Series
UPC	783936998572

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	90 Degree Liquidtight Non-Insulated Connector

Packaging

Carton	1
Package	10
Weight Per each	9.3

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA