



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## K150 1 1/2 STR Liqtite Conn *Hubbell--Killark*

|                  |   |
|------------------|---|
| Catalog Number   | K150  |
| Manufacturer     | Hubbell--Killark                                    |
| Description      | 1 1/2" Straight Liquidtight Connector Non-Insulated |
| Weight per unit  | 0.7500 (lbs/each)                                   |
| Product Category | Liquid Tight Fittings                               |

### Features

|                 |               |
|-----------------|---------------|
| insulation      | False         |
| Insulation Type | Non-Insulated |
| Material        | Steel         |

### Material, Color, and Finish

|        |             |
|--------|-------------|
| Color  | Gray        |
| Finish | Zinc Plated |

### Dimensions and Weight

|        |        |
|--------|--------|
| Length | 2-3/8  |
| Width  | 2-7/32 |

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 1 1/2 STR LIQTITE CONN   |
| extra long description | KLRK K150 1 1/2" STR LT CONNECTOR N  |
| Long Description       | 1 1/2" Straight Liquidtight Connector Non-Insulated  |
| Product Type           | 1 1/2" STR LT Connector Non-Insulated  |
| Special Features       | Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc. |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | KILLARK        |
| GTIN                      | 00783936991276 |
| Manufacturers Part Number | K150           |
| series                    | K Series       |
| UPC                       | 783936991276   |

### Taxonomies, Classifications, and Categories

|                      |  |
|----------------------|--|
| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS          |
| Type                 | Straight Liquidtight Non-Insulated Connector |

### Packaging

|                 |      |
|-----------------|------|
| Carton          | 1    |
| Package         | 1280 |
| Weight Per each | 0.75 |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location

environmental conditions  
standard

Hazardous locations  
UL, CSA