



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## K2009 2IN 90D Liqтите Conn *Hubbell--Killark*

Catalog Number	K2009
Manufacturer	Hubbell--Killark
Description	2" 90° Liquidtight Connector Non-Insulated
Weight per unit	2.6 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

insulation	False
Insulation Type	Non-Insulated
Material	Iron;Malleable

### Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

### Dimensions and Weight

Length	3-5/8
Width	2-7/8

### Descriptions

Description	2IN 90D LIQTITE CONN
extra long description	KLRK K2009 2" 90° LT CONNECTOR NON-
Long Description	2" 90° Liquidtight Connector Non-Insulated
Product Type	2" 90° LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

### Manufacturer Information

Brand	KILLARK
GTIN	00783936998602
Manufacturers Part Number	K2009
series	K Series
UPC	783936998602

### Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	90 Degree Liquidtight Non-Insulated Connector

### Packaging

Carton	1
Package	5
Weight Per each	2.57



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location

environmental conditions  
standard

Hazardous locations  
UL, CSA