

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



KL201 A:6, B:6 Alu Comp Splice *Abb Installation Products, Inc*

Catalog Number	KL201
Manufacturer	Abb Installation Products, Inc
Description	Aluminum 3-1/2 Inch Service Entrance Compression Splice For Wire Range - End A: 6 STR., 6 STR. Compact, Blue, End B: 6 STR., 6 STR. Compact, Blue, Die: 840. For AI to AI and AI to Cu Conductors.
Weight per unit	0.2110 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
connection	Compression
insulation	None
Material	Aluminum
Number of Conductors	2
Dimensions and Weight	
Size	3-1/2 Inch
Descriptions	
Description	A:6,B:6 ALU COMP SPLICE
extra long description	ABB KL20-1 AL SERVENTR SPLICE A:6 B
Long Description	Aluminum 3-1/2 Inch Service Entrance Compression Splice for Wire Range - End A: 6 Str., 6 Str. Compact, Blue, End B: 6 Str., 6 Str. Compact, Blue, Die: 840. For AL to AL and AL to CU Conductors.
Product Type	Al Serventr Splice A:6 B:4/0 3.5
Special Features	Splices large conductors required for commercial service, use as low cost reducing sleeve. All sizes can be installed with popular mechanical and hydraulic tools. Center stop assures proper conductor positioning. Quick identifications with color-coded foi caps
Manufacturer Information	
Brand	Blackburn Mechanical
GTIN	00783786050000
Manufacturers Part Number	KL20-1
LIPC.	783786050000

Mar

Brand	Blackburn Mechanical
GTIN	00783786050000
Manufacturers Part Number	KL20-1
UPC	783786050000

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Compression Splice Service Entrance



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pa	C	<i>(</i> 2	a	n	n
u		ľ	u		u
			IJ		J

Carton	25	
Package	250	
Weight Per each	0.211	

Uses, Certifications, and Standards

os, ooi tiiioatioiis, aiia otaiiaai	u o
Application	For Combinations of Aluminum-to-Aluminum and
	Aluminum-to-Copper Conductors
environmental conditions	All Seasons / Conditions
Mounting	None
standard	Passes the requirements of ANSI C119.4 / Passes the
	requirements of ANSI C119.4