



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## KL651 A:4/0, B:1-2 Alu Comp Splice

*Abb Installation Products, Inc*

Catalog Number	KL651
Manufacturer	Abb Installation Products, Inc
Description	Aluminum 3-1/2 Inch Service Entrance Compression Splice For Wire Range - End A: 4/0 Ascr, 4/0 STR., Red, End B: 2 Ascr, 1-2 STR., 1 STR. Compact, Red, Die: 840. For Al to Al and Al to Cu Conductors.
Weight per unit	0.1500 (lbs/each)
Product Category	Large Terminals & Connectors

### Features

connection	Compression
insulation	None
Material	Aluminum
Number of Conductors	2

### Dimensions and Weight

Size	3-1/2 Inch
------	------------

### Descriptions

Description	A:4/0,B:1-2 ALU COMP SPLICE
extra long description	ABB KL65-1 AL SERVENTR SPLICE A:4/0
Long Description	Aluminum 3-1/2 Inch Service Entrance Compression Splice for Wire Range - End A: 4/0 ASCR, 4/0 Str., Red, End B: 2 ASCR, 1-2 Str., 1 Str. Compact, Red, Die: 840. For AL to AL and AL to CU Conductors.
Product Type	Al Serventr Splice A:4/0 B:1-2 3.5
Special Features	Splices large conductors required for commercial service, use as low cost reducing sleeve. All sizes can be installed with popular mechanical and hydraulic tools. Center stop assures proper conductor positioning. Quick identifications with color-coded foil caps

### Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786050116
Manufacturers Part Number	KL65-1
UPC	783786050116

### Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Compression Splice Service Entrance



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	25
Package	250
Weight Per each	0.15

## Uses, Certifications, and Standards

Application	For Combinations of Aluminum-to-Aluminum and Aluminum-to-Copper Conductors
environmental conditions	All Seasons / Conditions
Mounting	None
standard	Passes the requirements of ANSI C119.4 / Passes the requirements of ANSI C119.4