



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



KLU1600 TD Class L Fuse *Bussmann Fuses*

Catalog Number	KLU1600
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class L Fuse, Klu, Fast-Acting, Current Limiting Fuse, 1600 A, Bladable Fuse, Interrupting Rating Of 200 Ka, 600 Vac
Weight per unit	6.0 (lbs/each)
Product Category	Current Limiting

Features

amperage rating	1600
connection	Bolted Blade End X Bolted Blade End
dimensions	3.0000 IN X 3.0000 IN X 1.7500 IN
Fuse Class	Class L
interrupt rating	200 kAIC at 600 Vac
media	Yes
Response Time	5 sec at 500%
Voltage Rating	600 V

Dimensions and Weight

Size	3.00 In Diameter X 10.75 In Length
------	------------------------------------

Descriptions

Description	TD CLASS L FUSE
extra long description	BUSS KLU-1600 LIMITRON TIME DELAY F
Features	Bussmann's broad line of UL Class L fuses includes the KRP-C-SP Low-Peak family of fuses offering unsurpassed dual-element, current-limiting, time-delay performance and interrupting ratings of 300kA RMS Sym. Complementing the Low-Peak family are our Limitron products offering both Fast-acting and economical time-delay performance in our KTU, KLU, and KRP-CL products
Long Description	Eaton Bussmann Series Class L fuse, KLU, fast-acting, current limiting fuse, 1600 A, bladable fuse, interrupting rating of 200 kA, 600 Vac
Product Type	Limitron Time Delay Fuse
Special Features	Indicating

Manufacturer Information

Brand	Eaton
GTIN	00051712135092
Manufacturers Part Number	KLU-1600
UPC	051712135092



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

Packaging

Carton	1
Weight Per each	5.95

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
Mounting	Bolt-on
standard	RoHS Compliant,CE Marked