Specifications







Eaton KRP-C-800SP

Eaton Bussmann Series Class L fuse, KRP-C, time-delay, current limiting fuse, 800 A, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc

General specifications	
PRODUCT NAME	Eaton Bussmann series KRP-C fuse
CATALOG NUMBER	KRP-C-800SP
UPC	051712605083
PRODUCT LENGTH/DEPTH	8.63 in
PRODUCT HEIGHT	2.53 in
PRODUCT WIDTH	2.53 in
PRODUCT WEIGHT	0.001 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant



Electrical rating	
AMPERAGE RATING	800 A
INTERRUPT RATING	300 kAIC at 600 Vac 100 kA at 300 kAIC Vdc
RESPONSE TIME	4 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

Physical details	
PACKAGING TYPE	Standard

General information	
CLASS	Class L
CONNECTION	Bolted blade end x bolted blade end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Small footprint

Resources	
CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93- 68-EEC2006
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
TECHNICAL DATA SHEETS	Bussmann series KRP-C 601 to 2000A Class L fuse data sheet No. 1008

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.

© 2025 Eaton. All Rights









Specifications







Eaton KRP-C-800SP

Eaton Bussmann Series Class L fuse, KRP-C, time-delay, current limiting fuse, 800 A, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc

General specifications	
PRODUCT NAME	Eaton Bussmann series KRP-C fuse
CATALOG NUMBER	KRP-C-800SP
UPC	051712605083
PRODUCT LENGTH/DEPTH	8.63 in
PRODUCT HEIGHT	2.53 in
PRODUCT WIDTH	2.53 in
PRODUCT WEIGHT	0.001 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant



Electrical rating	
AMPERAGE RATING	800 A
INTERRUPT RATING	300 kAIC at 600 Vac 100 kA at 300 kAIC Vdc
RESPONSE TIME	4 sec at 500%
VOLTAGE RATING	600 Vac, 300 Vdc

Physical details	
PACKAGING TYPE	Standard

General information	
CLASS	Class L
CONNECTION	Bolted blade end x bolted blade end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Small footprint

Resources	
CATALOGS	Low Voltage Branch Circuit Fuse Chapter Bussmann Full Line Catalog
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93- 68-EEC2006
COMPLIANCE INFORMATION	RoHS Search Tool
MULTIMEDIA	Bussmann series Fuseology
TECHNICAL DATA SHEETS	Bussmann series KRP-C 601 to 2000A Class L fuse data sheet No. 1008

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.

© 2025 Eaton. All Rights







