Pass and Seymour
**20A NEMA Plug L1020 - Black Back, White Front Body**
Part No. L1020P



Turnlok® Plug 3-Wire 20A 125/250V

## Features & Benefits

Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire.

Raised ribs provide non-slip gripping profile for turning to lock and unlock.

Impact- and corrosion-resistant durable nylon 6 shell material.

Scallop shell design provides non-slip gripping surface for insertion and withdrawal.

Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber.

Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.

Double dovetail design provides superior protection against cord pull-out forces.

Rounded back contour reduces snags and hang-ups on the job site.

Visible stamped NEMA configuration and device rating. New-design external cord grips provide visible assurance of safe and proper cord retention.

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007102048 | Country Of Origin | Mexico |
| Features | Locking | Application Sector | Commercial |
| Standard | UL 498, FEDSPEC | Warranty Type | 1-Year |
| Type | Plug | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 2.2 in | Product Length US | 2.57 in |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Connector Style | Locking | Flanged | No |
| Terminal Accommodation | #18 AWG - #10 AWG | Number of Wires | 3 |
| Amperage | 20 A | Number of Poles | 3-Way |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L10-20P |
| Number of Phases | 3 | Voltage | 125/250 V |

Pass and Seymour
**20A NEMA Plug L1020 - Black Back, White Front Body**
Part No. L1020P



Turnlok® Plug 3-Wire 20A 125/250V

## Features & Benefits

Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire.

Raised ribs provide non-slip gripping profile for turning to lock and unlock.

Impact- and corrosion-resistant durable nylon 6 shell material.

Scallop shell design provides non-slip gripping surface for insertion and withdrawal.

Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber.

Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.

Double dovetail design provides superior protection against cord pull-out forces.

Rounded back contour reduces snags and hang-ups on the job site.

Visible stamped NEMA configuration and device rating. New-design external cord grips provide visible assurance of safe and proper cord retention.

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007102048 | Country Of Origin | Mexico |
| Features | Locking | Application Sector | Commercial |
| Standard | UL 498, FEDSPEC | Warranty Type | 1-Year |
| Type | Plug | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 2.2 in | Product Length US | 2.57 in |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Connector Style | Locking | Flanged | No |
| Terminal Accommodation | #18 AWG - #10 AWG | Number of Wires | 3 |
| Amperage | 20 A | Number of Poles | 3-Way |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L10-20P |
| Number of Phases | 3 | Voltage | 125/250 V |