Pass and Seymour
**20A NEMA L1820 Single Receptacle**
Part No. L1820R



Receptacle Single 4-Wire 20A 120/208Volt Turnlok®

## Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007182057 | Country Of Origin | Mexico |
| Number of Receptacles | 1 | Features | Brass Mounting Strap, Impact Resistant |
| Outlet Type | Locking | Application Sector | Commercial |
| Wall Plate Included | No | Standard | UL 498, FEDSPEC |
| Warranty Type | 1-Year Limited Warranty | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 1.61 in | Product Depth US | 1.19 in |

| | |
|---|---|
| Product Height US | 2.29 in |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Connection Location | Back and Side | Phase | Three |
| Number of Wires | 4 | Amperage | 20 A |
| Number of Poles | 4-Way | Wire Size | 18 - 10 AWG |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L18-20R |
| Wire Connection Type | Screw Terminals | Voltage | 120/208 V |

Pass and Seymour
**20A NEMA L1820 Single Receptacle**
Part No. L1820R



Receptacle Single 4-Wire 20A 120/208Volt Turnlok®

## Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007182057 | Country Of Origin | Mexico |
| Number of Receptacles | 1 | Features | Brass Mounting Strap, Impact Resistant |
| Outlet Type | Locking | Application Sector | Commercial |
| Wall Plate Included | No | Standard | UL 498, FEDSPEC |
| Warranty Type | 1-Year Limited Warranty | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 1.61 in | Product Depth US | 1.19 in |

| | |
|---|---|
| Product Height US | 2.29 in |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Connection Location | Back and Side | Phase | Three |
| Number of Wires | 4 | Amperage | 20 A |
| Number of Poles | 4-Way | Wire Size | 18 - 10 AWG |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L18-20R |
| Wire Connection Type | Screw Terminals | Voltage | 120/208 V |