Pass and Seymour
**30A L2130 Connector - Black Back, White Front Body**
Part No. L2130C



Turnlok® Connector 5-Wire 30A 3-Phase 120/208V

## Features & Benefits

- Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire.
- Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.
- Raised ribs provide non-slip gripping profile for turning to lock and unlock.
- Double dovetail design provides superior protection against cord pull-out forces.
- Impact- and corrosion-resistant durable nylon 6 shell material.
- Rounded back contour reduces snags and hang-ups on the job site.
- Scallop shell design provides non-slip gripping surface for insertion and withdrawal.
- Visible stamped NEMA configuration and device rating.
- New-design external cord grips provide visible assurance of safe and proper cord retention.
- Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber.

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007213010 | Country Of Origin | Mexico |
| Features | Corrosion Resistant | Application Sector | Industrial |
| Standard | UL 498, FEDSPEC | Warranty Type | 1-Year |
| Type | Connector | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 2.2 in | Product Length US | 3.33 in |

## Listing Agencies / 3rd Party Agencies

| | | | |
|---|---|---|---|
| cULus ListingNumber | 146159 | cULus Listed | Yes |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Connector Style | Locking | Flanged | No |
| Terminal Accommodation | #18 AWG - #10 AWG | Number of Wires | 5 |
| Amperage | 30 A | Number of Poles | 3-Way |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L21-30R |
| Number of Phases | 3 | Voltage | 120/208 V |

Pass and Seymour
**30A L2130 Connector - Black Back, White Front Body**
Part No. L2130C



Turnlok® Connector 5-Wire 30A 3-Phase 120/208V

## Features & Benefits

- Quick-thread assembly screws and cord-grip screws come backed-out, ready-to-wire.
- Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.
- Raised ribs provide non-slip gripping profile for turning to lock and unlock.
- Double dovetail design provides superior protection against cord pull-out forces.
- Impact- and corrosion-resistant durable nylon 6 shell material.
- Rounded back contour reduces snags and hang-ups on the job site.
- Scallop shell design provides non-slip gripping surface for insertion and withdrawal.
- Visible stamped NEMA configuration and device rating.
- New-design external cord grips provide visible assurance of safe and proper cord retention.
- Integral flexible rubber cord grommet conforms to and seals around SO cord to provide protection from oils, water, or chips entering wiring chamber.

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Pass & Seymour | Color | Black |
| UPC Number | 785007213010 | Country Of Origin | Mexico |
| Features | Corrosion Resistant | Application Sector | Industrial |
| Standard | UL 498, FEDSPEC | Warranty Type | 1-Year |
| Type | Connector | | |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 2.2 in | Product Length US | 3.33 in |

## Listing Agencies / 3rd Party Agencies

| | | | |
|---|---|---|---|
| cULus ListingNumber | 146159 | cULus Listed | Yes |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Connector Style | Locking | Flanged | No |
| Terminal Accommodation | #18 AWG - #10 AWG | Number of Wires | 5 |
| Amperage | 30 A | Number of Poles | 3-Way |
| Indoor/Outdoor | Indoor | NEMA Configuration Code | L21-30R |
| Number of Phases | 3 | Voltage | 120/208 V |