

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



L30N 3/0 1/2" 2-Hole Long Barrel Compression Lug Nsi Industries

Catalog Number	L30N
Manufacturer	Nsi Industries
Description	2 Hole Long Barrel Copper Compression Lug 3/0 Awg - 1/2" Bolt Long Barrel Copper Compression Lugs Are Produced From High Conductivity Copper Tubing. Allows Easy Inspection Of The Termination to Assure Complete Cable Insertion. Tin-Plated to Provide Corrosion and Low Contact Resistance. Marked With Die Index and Color Coded. Listed For 35KV Maximum When Properly Installed. Rated 600V. Culus 486A/B Listed. UL467 Listed On Sizes 6 Awg - 3/0 Awg. Temperature Rating 90 Degrees C.
Weight per unit	0.1600 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Cable Size	3/0 AWG (STR)
Material	Copper
Number of Holes	2
Stud Size	1/2
Voltage Rating	600 V
Warranty	
Material, Color, and Finish	
Color	Orange
Finish	Tin Plated
Dimensions and Weight	
Size	L=4.65 - W=.900 - OD=.620 - ID=.490



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	3/0 1/2" 2-HOLE LONG BARREL COMPRESSION LUG
extra long description	NSI L30N CU CMP Lug Long 3/0 AWG Ne
Features	2 Hole Long Barrel Copper Compression Lug 3/0 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C.
Long Description	2 Hole Long Barrel Copper Compression Lug 3/0 AWG - 1/2" Bolt Long Barrel Copper Compression Lugs are produced from high conductivity copper tubing. Allows easy inspection of the termination to assure complete cable insertion. Tin-plated to provide corrosion and low contact resistance. Marked with die index and color coded. Listed for 35KV maximum when properly installed. Rated 600V. cULus 486A/B Listed. UL467 Listed on sizes 6 AWG - 3/0 AWG. Temperature rating 90 degrees C.
Product Type	
Special Features	3/0 AWG (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing
Manufacturer Information	
Brand	NSi
GTIN	00662381035110
Manufacturers Part Number	L30N
UPC	662381035110
Taxonomies, Classifications, and (Categories
Category Description	
Туре	Long Barrel - Two Hole
Packaging	
Carton	1
Package	25
Weight Per each	0.16
Uses, Certifications, and Standard	S
Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
Mounting	1/2 Mounting Holes
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)