

ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LBH100 4" LBH Conduit Body Crouse-Hinds

Catalog Number	LBH100
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet LBH Conduit Outlet Body With Cover, Feraloy Iron Alloy, 4"
Weight per unit	67.9 (lbs/each)
Product Category	Bodies & Covers
Features	
connection	Threaded
dimensions	23.5600 IN X 7.1300 IN X 24.0000 IN
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	11-3/4
Hub Size	4 in
Width	7-1/8
Descriptions	
Description	4" LBH CONDUIT BODY
extra long description	CRS-H LBH100 4 CNDT OUTLET BODY
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet LBH conduit outlet body with cover, Feraloy iron alloy, 4"
Product Type	4 CNDT Outlet Body
Special Features	With Cover
Manufacturer Information	
Brand	Eaton
GTIN	00782274519906
Manufacturers Part Number	LBH100
UPC	782274519906



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Туре	Conduit outlet body with cover
Packaging	
Carton	1
Weight Per each	67.9499
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2