

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LBH80 3" LBH Exprf Conduit Body Crouse-Hinds

Catalog Number	LBH80
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet LBH Conduit Outlet Body With Cover, Feraloy Iron Alloy, 3"
Weight per unit	33.9 (lbs/each)
Product Category	Bodies & Covers
- eatures	
connection	Threaded
dimensions	15.6300 IN X 5.6300 IN X 15.7500 IN
Vaterial, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	9-1/2
Hub Size	3 in
Width	5-5/8
Descriptions	
Description	3" LBH EXPRF CONDUIT BODY
extra long description	CRS-H LBH80 3 CNDT OUTLET BODY
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet LBH conduit outlet body with cover, Feraloy iron alloy, 3"
Product Type	3 CNDT Outlet Body
Special Features	With Cover
Vanufacturer Information	
Brand	Eaton
GTIN	00782274519708
Manufacturers Part Number	LBH80
UPC	782274519708



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
	Conduit outlet body with cover
Packaging	
Carton	1
Weight Per each	33.9
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2