



LED Dimmable Recessed Retrofits

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

Limitless options for the following applications:

- Dimmable 6", 5" & 4" downlight applications

Great features and benefits:

- 120W, 85W, 75W, 65W and 50W BR40/BR30/R20 downlight replacement options
- Excellent color consistency (CRI)
- Smooth, uniform dimming from 100% - 0.5%
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- Available in 2700K, 3000K, 4100K and 5000K
- Easy installation — pigtail and spring clips



4" Dimmable HiCRI Recessed Retrofit



5/6" Dimmable HiCRI Recessed Retrofit

90 CRI
50 R9



4" Dimmable Recessed Retrofit



5/6" Dimmable Recessed Retrofit



LED
we know light.™





LED Dimmable Recessed Retrofits Specifications

| | |
|------------|--|
| LED | 35,000 hours average rated life, 120 volts |
|------------|--|

Applications:

Ideal for dimmable 6", 5" & 4" downlight applications



Perfect for retrofit or new construction recessed downlight applications

Features and Benefits

- 5/6" unit ideal for replacing dimmable 65W, 85W and 120W incandescent alternatives in 5" and 6" recessed cans
- 4" unit ideal for replacing 50W and 75W incandescent alternatives in a 4" recessed can
- Excellent Color Consistency and CRI
- Smooth, uniform dimming
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- UL approved for damp locations
- Easy installation and integrated trim
- Shatter Resistant



LDRACCGU24 - GU24 Adapter

| | |
|----------------|------|
| Catalog Number | |
| Notes | Type |



Specifications

| | 14W | 11W | 10W | 9W |
|--------------------------|------------|------------|------------|------------|
| Recessed Downlight Size: | 5", 6" | 5", 6" | 4" | 4" |
| Input Line Voltage: | 120 VAC | 120 VAC | 120 VAC | 120 VAC |
| Input Power | 14 W | 11 W | 10 W | 9 W |
| Input Line Frequency | 50/60HZ | 50/60HZ | 50/60HZ | 50/60HZ |
| Lamp Life (Rated) | 35,000 hrs | 35,000 hrs | 35,000 hrs | 35,000 hrs |
| Minimum Starting Temp | -30°C | -30°C | -30°C | -30°C |

IC-rated for direct contact with insulation



- LED11DR5627K
- LED11DR5630K
- LED11DR5641K
- LED11DR5650K
- LED14DR5627K
- LED14DR5630K
- LED14DR5641K
- LED14DR5650K



- LED10DR427K
- LED10DR430K
- LED10DR435K
- LED10DR441K
- LED10DR450K



- L11DR56D3527K95
- L11DR56D3530K95



- L9DR4D3527K95
- L9DR4D3530K95



5 YEAR WARRANTY*

*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP AUG 2017/WF72602.ALL





LED Dimmable Recessed Retrofits Specifications

Smooth Uniform Dimming

5/6" Recessed Retrofits

| Item # | ENERGY STAR rated | Description | Life Hours | Replacement | Voltage | Wattage | Lumens | LPW | CCT | CRI | Case Qty |
|--|-------------------|---|------------|-------------|---------|---------|--------|------|-------|-----|----------|
| Downlight Retrofits compatible with 5/6" recessed cans | | | | | | | | | | | |
| LED14DR5627K | ★ | LED 14W 5/6" Recessed Downlight - 2700K | 35,000 | 120 | 120 | 14 | 1250 | 89.3 | 2700K | 80 | 6 |
| LED14DR5630K | ★ | LED 14W 5/6" Recessed Downlight - 3000K | 35,000 | 120 | 120 | 14 | 1300 | 92.9 | 3000K | 80 | 6 |
| LED14DR5641K | ★ | LED 14W 5/6" Recessed Downlight - 4100K | 35,000 | 120 | 120 | 14 | 1300 | 92.9 | 4100K | 80 | 6 |
| LED14DR5650K | ★ | LED 14W 5/6" Recessed Downlight - 5000K | 35,000 | 120 | 120 | 14 | 1350 | 96.4 | 5000K | 80 | 6 |
| LED11DR5627K | ★ | LED 11W 5/6" Recessed Downlight - 2700K | 35,000 | 85 | 120 | 11 | 800 | 72.7 | 2700K | 80 | 6 |
| LED11DR5630K | ★ | LED 11W 5/6" Recessed Downlight - 3000K | 35,000 | 85 | 120 | 11 | 850 | 77.3 | 3000K | 80 | 6 |
| LED11DR5641K | ★ | LED 11W 5/6" Recessed Downlight - 4100K | 35,000 | 85 | 120 | 11 | 900 | 81.8 | 4100K | 80 | 6 |
| LED11DR5650K | ★ | LED 11W 5/6" Recessed Downlight - 5000K | 35,000 | 85 | 120 | 11 | 950 | 86.4 | 5000K | 80 | 6 |
| Hi CRI Downlight Retrofits compatible with 5/6" recessed cans | | | | | | | | | | | |
| L11DR56D3527K95** | ★ | LED 11W 5/6" Recessed Downlight - 2700K | 35,000 | 65 | 120 | 11 | 700 | 63.6 | 2700K | 90 | 6 |
| L11DR56D3530K95** | ★ | LED 11W 5/6" Recessed Downlight - 3000K | 35,000 | 65 | 120 | 11 | 750 | 68.2 | 3000K | 90 | 6 |

4" Recessed Retrofits

| | | | | | | | | | | | |
|--|---|---------------------------------------|--------|----|-----|----|-----|------|-------|----|---|
| Downlight Retrofits compatible with 4" recessed cans | | | | | | | | | | | |
| LED10DR427K | ★ | LED 10W 4" Recessed Downlight - 2700K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 2700K | 80 | 6 |
| LED10DR430K | ★ | LED 10W 4" Recessed Downlight - 3000K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 3000K | 80 | 6 |
| LED10DR435K | | LED 10W 4" Recessed Downlight - 3500K | 35,000 | 75 | 120 | 10 | 620 | 62.0 | 3500K | 80 | 6 |
| LED10DR441K | ★ | LED 10W 4" Recessed Downlight - 4100K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 4100K | 80 | 6 |
| LED10DR450K | ★ | LED 10W 4" Recessed Downlight - 5000K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 5000K | 80 | 6 |
| Hi CRI Downlight Retrofits compatible with 4" recessed cans | | | | | | | | | | | |
| L9DR4D3527K95** | ★ | LED 9W 4" Recessed Downlight - 2700K | 35,000 | 50 | 120 | 9 | 550 | 61.1 | 2700K | 90 | 6 |
| L9DR4D3530K95** | ★ | LED 9W 4" Recessed Downlight - 3000K | 35,000 | 50 | 120 | 9 | 550 | 61.1 | 3000K | 90 | 6 |

Accessory

LDRACCGU24 GU24 Adapter

*JAB Compliant

+All Plastic Body



5 YEAR WARRANTY*

*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP AUG 2017/WF72602.ALL



CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps and our

integrated technology and manufacturing

provides **expedited time-to-market.** With TCP, you can

count on unique lighting products designed to meet very specific needs—

lighting that transforms your surroundings and envelopes you in warmth—

lighting that generates beauty with every flip of the switch.

LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | F: 877-487-0516



LED Dimmable Recessed Retrofits

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

Limitless options for the following applications:

- Dimmable 6", 5" & 4" downlight applications

Great features and benefits:

- 120W, 85W, 75W, 65W and 50W BR40/BR30/R20 downlight replacement options
- Excellent color consistency (CRI)
- Smooth, uniform dimming from 100% - 0.5%
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- Available in 2700K, 3000K, 4100K and 5000K
- Easy installation — pigtail and spring clips



4" Dimmable HiCRI Recessed Retrofit



5/6" Dimmable HiCRI Recessed Retrofit

90 CRI
50 R9



4" Dimmable Recessed Retrofit



5/6" Dimmable Recessed Retrofit



LED
we know light.™





LED Dimmable Recessed Retrofits Specifications

| | |
|------------|--|
| LED | 35,000 hours average rated life, 120 volts |
|------------|--|

Applications:

Ideal for dimmable 6", 5" & 4" downlight applications



Perfect for retrofit or new construction recessed downlight applications

Features and Benefits

- 5/6" unit ideal for replacing dimmable 65W, 85W and 120W incandescent alternatives in 5" and 6" recessed cans
- 4" unit ideal for replacing 50W and 75W incandescent alternatives in a 4" recessed can
- Excellent Color Consistency and CRI
- Smooth, uniform dimming
- Highly efficient LEDs and Driver
- Long Life: 35,000 hours
- UL approved for damp locations
- Easy installation and integrated trim
- Shatter Resistant



LDRACCGU24 – GU24 Adapter

| | |
|----------------|------|
| Catalog Number | |
| Notes | Type |



Specifications

| | 14W | 11W | 10W | 9W |
|--------------------------|------------|------------|------------|------------|
| Recessed Downlight Size: | 5", 6" | 5", 6" | 4" | 4" |
| Input Line Voltage: | 120 VAC | 120 VAC | 120 VAC | 120 VAC |
| Input Power | 14 W | 11 W | 10 W | 9 W |
| Input Line Frequency | 50/60HZ | 50/60HZ | 50/60HZ | 50/60HZ |
| Lamp Life (Rated) | 35,000 hrs | 35,000 hrs | 35,000 hrs | 35,000 hrs |
| Minimum Starting Temp | -30°C | -30°C | -30°C | -30°C |

IC-rated for direct contact with insulation



- LED11DR5627K
- LED11DR5630K
- LED11DR5641K
- LED11DR5650K
- LED14DR5627K
- LED14DR5630K
- LED14DR5641K
- LED14DR5650K



- LED10DR427K
- LED10DR430K
- LED10DR435K
- LED10DR441K
- LED10DR450K



- L11DR56D3527K95
- L11DR56D3530K95



- L9DR4D3527K95
- L9DR4D3530K95



5 YEAR WARRANTY*

*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP AUG 2017/WF72602.ALL





LED Dimmable Recessed Retrofits Specifications

Smooth Uniform Dimming

5/6" Recessed Retrofits

| Item # | ENERGY STAR rated | Description | Life Hours | Replacement | Voltage | Wattage | Lumens | LPW | CCT | CRI | Case Qty |
|--|-------------------|---|------------|-------------|---------|---------|--------|------|-------|-----|----------|
| Downlight Retrofits compatible with 5/6" recessed cans | | | | | | | | | | | |
| LED14DR5627K | ★ | LED 14W 5/6" Recessed Downlight - 2700K | 35,000 | 120 | 120 | 14 | 1250 | 89.3 | 2700K | 80 | 6 |
| LED14DR5630K | ★ | LED 14W 5/6" Recessed Downlight - 3000K | 35,000 | 120 | 120 | 14 | 1300 | 92.9 | 3000K | 80 | 6 |
| LED14DR5641K | ★ | LED 14W 5/6" Recessed Downlight - 4100K | 35,000 | 120 | 120 | 14 | 1300 | 92.9 | 4100K | 80 | 6 |
| LED14DR5650K | ★ | LED 14W 5/6" Recessed Downlight - 5000K | 35,000 | 120 | 120 | 14 | 1350 | 96.4 | 5000K | 80 | 6 |
| LED11DR5627K | ★ | LED 11W 5/6" Recessed Downlight - 2700K | 35,000 | 85 | 120 | 11 | 800 | 72.7 | 2700K | 80 | 6 |
| LED11DR5630K | ★ | LED 11W 5/6" Recessed Downlight - 3000K | 35,000 | 85 | 120 | 11 | 850 | 77.3 | 3000K | 80 | 6 |
| LED11DR5641K | ★ | LED 11W 5/6" Recessed Downlight - 4100K | 35,000 | 85 | 120 | 11 | 900 | 81.8 | 4100K | 80 | 6 |
| LED11DR5650K | ★ | LED 11W 5/6" Recessed Downlight - 5000K | 35,000 | 85 | 120 | 11 | 950 | 86.4 | 5000K | 80 | 6 |
| Hi CRI Downlight Retrofits compatible with 5/6" recessed cans | | | | | | | | | | | |
| L11DR56D3527K95** | ★ | LED 11W 5/6" Recessed Downlight - 2700K | 35,000 | 65 | 120 | 11 | 700 | 63.6 | 2700K | 90 | 6 |
| L11DR56D3530K95** | ★ | LED 11W 5/6" Recessed Downlight - 3000K | 35,000 | 65 | 120 | 11 | 750 | 68.2 | 3000K | 90 | 6 |

4" Recessed Retrofits

| | | | | | | | | | | | |
|--|---|---------------------------------------|--------|----|-----|----|-----|------|-------|----|---|
| Downlight Retrofits compatible with 4" recessed cans | | | | | | | | | | | |
| LED10DR427K | ★ | LED 10W 4" Recessed Downlight - 2700K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 2700K | 80 | 6 |
| LED10DR430K | ★ | LED 10W 4" Recessed Downlight - 3000K | 35,000 | 75 | 120 | 10 | 750 | 75.0 | 3000K | 80 | 6 |
| LED10DR435K | | LED 10W 4" Recessed Downlight - 3500K | 35,000 | 75 | 120 | 10 | 620 | 62.0 | 3500K | 80 | 6 |
| LED10DR441K | ★ | LED 10W 4" Recessed Downlight - 4100K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 4100K | 80 | 6 |
| LED10DR450K | ★ | LED 10W 4" Recessed Downlight - 5000K | 35,000 | 75 | 120 | 10 | 800 | 80.0 | 5000K | 80 | 6 |
| Hi CRI Downlight Retrofits compatible with 4" recessed cans | | | | | | | | | | | |
| L9DR4D3527K95** | ★ | LED 9W 4" Recessed Downlight - 2700K | 35,000 | 50 | 120 | 9 | 550 | 61.1 | 2700K | 90 | 6 |
| L9DR4D3530K95** | ★ | LED 9W 4" Recessed Downlight - 3000K | 35,000 | 50 | 120 | 9 | 550 | 61.1 | 3000K | 90 | 6 |

Accessory

LDRACCGU24 GU24 Adapter

*JAB Compliant

+All Plastic Body



5 YEAR WARRANTY*

*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP AUG 2017/WF72602.ALL



CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps and our

integrated technology and manufacturing

provides **expedited time-to-market.** With TCP, you can

count on unique lighting products designed to meet very specific needs—

lighting that transforms your surroundings and envelopes you in warmth—

lighting that generates beauty with every flip of the switch.

LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | F: 877-487-0516