



# Elite LED Deco Lamps

TCP Elite Decorative lamps closely mimic the look and feel of incandescent but last much longer.

## Limitless options for the following applications:

- Accent and decorative lighting
- Chandeliers
- Ceiling fans
- Indoor/outdoor fixtures

## Great features and benefits:

- Energy efficient: 80% energy savings
- Replaces 25W and 40W incandescent lamps
- Smooth, uniform dimming—perfect for chandeliers
- Long life: 25,000 hours
- Excellent color consistency and high color rendering (CRI)
- UL damp location rated—excellent for use in outdoor applications



Candelabra G16 Globe\*  
Frosted and Clear

Candelabra Blunt Tip\*  
Frosted and Clear

Candelabra Flame Tip\*  
Clear

\* Also available in an E26 base (frosted and clear)

LED  
we know light.™





# LED ELITE Series LED Dimmable Decorative Series Specifications


|            |  |
|------------|--|
| <b>LED</b> | 25,000 hours average rated life, 120 volts |
|------------|--|

## Applications

Ideal for decorative dimming applications. Suitable for outdoor fixtures. Also perfect for applications with hard to reach areas, vibration, and frequent starts.

### Accent and decorative lighting including:

- + Chandeliers
- + Ceiling Fans
- + Decorative
- + Indoor Fixtures
- + Outdoor Fixtures
- + Wall Scones



### Light output equivalency:

5w = 40w  
4w = 25w

## Features and Benefits

- Long life: 25,000 hours — no more bulb replacements
  - Fully dimmable, brilliant LED light
  - Excellent white color consistency from bulb to bulb
  - UL approved for dry and damp locations
  - Available in E12 and E26 base
- \* Three or more lamps per dimming circuit is recommended for optimal dimming*


|                |  |
|----------------|--|
| Catalog Number |  |
|----------------|--|

|       |      |
|-------|------|
| Notes | Type |
|-------|------|




## Specifications (at full brightness)

|                             |            |
|-----------------------------|------------|
| Input Line Voltage: .....   | 120VAC     |
| Input Line Frequency .....  | 60HZ       |
| Lamp Life (Rated) .....     | 25,000 hrs |
| Minimum Starting Temp ..... | -30°C      |
| Maximum Operating Temp..... | 40°C       |
| UL/cUL Listed .....         | Yes        |
| Power Factor .....          | 92%        |
| CRI .....                   | 80         |



LED5E12G1627K  
LED4E12G1627K



LED5E26G1627K  
LED4E26G1627K



LED5E12B1127K  
LED5E12B1130K  
LED5E12B1150K  
LED4E12B1124K  
LED4E12B1127K  
LED4E12B1150K




LED5E26B1127K  
LED5E26B1130K  
LED4E26B1124K  
LED4E26B1127K




LED5E12F1127K  
LED4E12F1127K



LED5E26F1127K  
LED4E26F1127K



LED5E12G1627KF  
LED4E12G1627KF



LED5E26G1627KF  
LED4E26G1627KF



LED5E12B1124KF  
LED5E12B1127KF  
LED5E12B1150KF  
LED4E12B1127KF



LED5E26B1127KF  
LED4E26B1127KF



LED5E26F1127KF  
LED4E26F1127KF




**5 YEAR WARRANTY**

**RoHS COMPLIANCE**

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)



# LED ELITE Series LED Dimmable Decorative Series Specifications

| Warranties and Certifications:   | Item #   | Description  | Voltage | Wattage | Wattage Equivalent | M.O.L. (inches) | Diameter (inches) | Lumens | LPW   | CCT   | CRI |  |
|--|--|--|---------|---------|--------------------|-----------------|-------------------|--------|-------|-------|-----|--|
| <br><b>5 YEAR WARRANTY</b><br><b>RoHS COMPLIANT</b> | <b>5W Decorative Lamps</b>                           |  |         |         |                    |                 |                   |        |       |       |     |  |
|  | LED5E12G1627K  | LED 5W DIMMABLE CANDELABRA G16 GLOBE - 2700K         | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26G1627K  | LED 5W DIMMABLE G16 GLOBE - 2700K                    | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12G1627KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED G16 GLOBE - 2700K | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26G1627KF                                       | LED 5W DIMMABLE FROSTED G16 GLOBE - 2700K            | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12B1127K  | LED 5W DIMMABLE CANDELABRA BLUNT TIP - 2700K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12B1130K  | LED 5W DIMMABLE CANDELABRA BLUNT TIP - 3000K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 375    | 75    | 3000K | 80  |  |
|  | LED5E12B1150K  | LED 5W DIMMABLE CANDELABRA BLUNT TIP - 5000K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 400    | 80    | 5000K | 80  |  |
|  | LED5E26B1127K  | LED 5W DIMMABLE BLUNT TIP - 2700K                    | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26B1130K  | LED 5W DIMMABLE BLUNT TIP - 3000K                    | 120     | 5.0     | 40W                | 3.8             | 1.4               | 375    | 75    | 3000K | 80  |  |
|  | LED5E12B1124KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 2400K | 120     | 5.0     | 40W                | 3.8             | 1.4               | 300    | 60    | 2400K | 80  |  |
|  | LED5E12B1127KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 2700K | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12B1150KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 5000K | 120     | 5.0     | 40W                | 3.8             | 1.4               | 400    | 80    | 5000K | 80  |  |
|  | LED5E26B1127KF                                       | LED 5W DIMMABLE FROSTED BLUNT TIP - 2700K            | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12F1127K  | LED 5W DIMMABLE CANDELABRA FLAME TIP - 2700K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26F1127K  | LED 5W DIMMABLE FLAME TIP - 2700K                    | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26F1127KF                                       | LED 5W DIMMABLE FROSTED FLAME TIP - 2700K            | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | <b>4W Decorative Lamps</b>                           |  |         |         |                    |                 |                   |        |       |       |     |  |
|  | LED4E12G1627K  | LED 4W DIMMABLE CANDELABRA G16 GLOBE - 2700K         | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E26G1627K  | LED 4W DIMMABLE G16 GLOBE - 2700K                    | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E12G1627KF                                       | LED 4W DIMMABLE CANDELABRA FROSTED G16 GLOBE - 2700K | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E26G1627KF                                       | LED 4W DIMMABLE FROSTED G16 GLOBE - 2700K            | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E12B1124K  | LED 4W DIMMABLE CANDELABRA BLUNT TIP - 2400K         | 120     | 4.0     | 25W                | 3.8             | 1.4               | 200    | 50    | 2400K | 80  |  |
|  | LED4E12B1127K  | LED 4W DIMMABLE CANDELABRA BLUNT TIP - 2700K         | 120     | 4.0     | 25W                | 3.8             | 1.4               | 260    | 65    | 2700K | 80  |  |
|  | LED4E12B1150K  | LED 4W DIMMABLE CANDELABRA BLUNT TIP - 5000K         | 120     | 4.0     | 25W                | 3.8             | 1.4               | 280    | 70    | 5000K | 80  |  |
|  | LED4E26B1124K  | LED 4W DIMMABLE BLUNT TIP - 2400K                    | 120     | 4.0     | 25W                | 3.8             | 1.4               | 200    | 50    | 2400K | 80  |  |
| LED4E26B1127K  | LED 4W DIMMABLE BLUNT TIP - 2700K                    | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E12B1127KF   | LED 4W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 2700K | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E26B1127KF   | LED 4W DIMMABLE FROSTED BLUNT TIP - 2700K            | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E12F1127K  | LED 4W DIMMABLE CANDELABRA FLAME TIP - 2700K         | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E26F1127K  | LED 4W DIMMABLE FLAME TIP - 2700K                    | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E26F1127KF   | LED 4W DIMMABLE FROSTED FLAME TIP - 2700K            | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

# CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps. Our

**integrated technology and manufacturing** provides

**expedited time-to-market.** With TCP, you can count on

unique lighting products designed to meet very specific needs—lighting that

transforms your surroundings and envelopes you in warmth—**lighting**

**that generates beauty** with every flip of the switch.

# LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516



# Elite LED Deco Lamps

TCP Elite Decorative lamps closely mimic the look and feel of incandescent but last much longer.

## Limitless options for the following applications:

- Accent and decorative lighting
- Chandeliers
- Ceiling fans
- Indoor/outdoor fixtures

## Great features and benefits:

- Energy efficient: 80% energy savings
- Replaces 25W and 40W incandescent lamps
- Smooth, uniform dimming—perfect for chandeliers
- Long life: 25,000 hours
- Excellent color consistency and high color rendering (CRI)
- UL damp location rated—excellent for use in outdoor applications



Candelabra G16 Globe\*  
Frosted and Clear

Candelabra Blunt Tip\*  
Frosted and Clear

Candelabra Flame Tip\*  
Clear

\* Also available in an E26 base (frosted and clear)

LED  
we know light.™





# LED ELITE Series LED Dimmable Decorative Series Specifications


|            |  |
|------------|--|
| <b>LED</b> | 25,000 hours average rated life, 120 volts |
|------------|--|

## Applications

Ideal for decorative dimming applications. Suitable for outdoor fixtures. Also perfect for applications with hard to reach areas, vibration, and frequent starts.

### Accent and decorative lighting including:

- + Chandeliers
- + Ceiling Fans
- + Decorative
- + Indoor Fixtures
- + Outdoor Fixtures
- + Wall Scones



### Light output equivalency:

5w = 40w  
4w = 25w

## Features and Benefits

- Long life: 25,000 hours — no more bulb replacements
  - Fully dimmable, brilliant LED light
  - Excellent white color consistency from bulb to bulb
  - UL approved for dry and damp locations
  - Available in E12 and E26 base
- \* Three or more lamps per dimming circuit is recommended for optimal dimming*


|                |  |
|----------------|--|
| Catalog Number |  |
|----------------|--|

|       |      |
|-------|------|
| Notes | Type |
|-------|------|




## Specifications (at full brightness)

|                        |            |
|------------------------|------------|
| Input Line Voltage:    | 120VAC     |
| Input Line Frequency   | 60HZ       |
| Lamp Life (Rated)      | 25,000 hrs |
| Minimum Starting Temp  | -30°C      |
| Maximum Operating Temp | 40°C       |
| UL/cUL Listed          | Yes        |
| Power Factor           | 92%        |
| CRI                    | 80         |



LED5E12G1627K  
LED4E12G1627K



LED5E26G1627K  
LED4E26G1627K



LED5E12B1127K  
LED5E12B1130K  
LED5E12B1150K  
LED4E12B1124K  
LED4E12B1127K  
LED4E12B1150K




LED5E26B1127K  
LED5E26B1130K  
LED4E26B1124K  
LED4E26B1127K




LED5E12F1127K  
LED4E12F1127K



LED5E26F1127K  
LED4E26F1127K



LED5E12G1627KF  
LED4E12G1627KF



LED5E26G1627KF  
LED4E26G1627KF



LED5E12B1124KF  
LED5E12B1127KF  
LED5E12B1150KF  
LED4E12B1127KF



LED5E26B1127KF  
LED4E26B1127KF



LED5E26F1127KF  
LED4E26F1127KF




5 YEAR WARRANTY

RoHS COMPLIANCE

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)



# LED ELITE Series LED Dimmable Decorative Series Specifications

| Warranties and Certifications:   | Item #   | Description  | Voltage | Wattage | Wattage Equivalent | M.O.L. (inches) | Diameter (inches) | Lumens | LPW   | CCT   | CRI |  |
|--|--|--|---------|---------|--------------------|-----------------|-------------------|--------|-------|-------|-----|--|
| <br><b>5 YEAR WARRANTY</b><br><b>RoHS COMPLIANT</b> | <b>5W Decorative Lamps</b>                           |  |         |         |                    |                 |                   |        |       |       |     |  |
|  | LED5E12G1627K  | LED 5W DIMMABLE CANDELABRA G16 GLOBE - 2700K         | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26G1627K  | LED 5W DIMMABLE G16 GLOBE - 2700K                    | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12G1627KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED G16 GLOBE - 2700K | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26G1627KF                                       | LED 5W DIMMABLE FROSTED G16 GLOBE - 2700K            | 120     | 5.0     | 40W                | 3.5             | 2.0               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12B1127K  | LED 5W DIMMABLE CANDELABRA BLUNT TIP - 2700K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12B1130K  | LED 5W DIMMABLE CANDELABRA BLUNT TIP - 3000K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 375    | 75    | 3000K | 80  |  |
|  | LED5E12B1150K  | LED 5W DIMMABLE CANDELABRA BLUNT TIP - 5000K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 400    | 80    | 5000K | 80  |  |
|  | LED5E26B1127K  | LED 5W DIMMABLE BLUNT TIP - 2700K                    | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26B1130K  | LED 5W DIMMABLE BLUNT TIP - 3000K                    | 120     | 5.0     | 40W                | 3.8             | 1.4               | 375    | 75    | 3000K | 80  |  |
|  | LED5E12B1124KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 2400K | 120     | 5.0     | 40W                | 3.8             | 1.4               | 300    | 60    | 2400K | 80  |  |
|  | LED5E12B1127KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 2700K | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12B1150KF                                       | LED 5W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 5000K | 120     | 5.0     | 40W                | 3.8             | 1.4               | 400    | 80    | 5000K | 80  |  |
|  | LED5E26B1127KF                                       | LED 5W DIMMABLE FROSTED BLUNT TIP - 2700K            | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E12F1127K  | LED 5W DIMMABLE CANDELABRA FLAME TIP - 2700K         | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26F1127K  | LED 5W DIMMABLE FLAME TIP - 2700K                    | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | LED5E26F1127KF                                       | LED 5W DIMMABLE FROSTED FLAME TIP - 2700K            | 120     | 5.0     | 40W                | 3.8             | 1.4               | 350    | 70    | 2700K | 80  |  |
|  | <b>4W Decorative Lamps</b>                           |  |         |         |                    |                 |                   |        |       |       |     |  |
|  | LED4E12G1627K  | LED 4W DIMMABLE CANDELABRA G16 GLOBE - 2700K         | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E26G1627K  | LED 4W DIMMABLE G16 GLOBE - 2700K                    | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E12G1627KF                                       | LED 4W DIMMABLE CANDELABRA FROSTED G16 GLOBE - 2700K | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E26G1627KF                                       | LED 4W DIMMABLE FROSTED G16 GLOBE - 2700K            | 120     | 4.0     | 25W                | 3.5             | 2.0               | 280    | 70    | 2700K | 80  |  |
|  | LED4E12B1124K  | LED 4W DIMMABLE CANDELABRA BLUNT TIP - 2400K         | 120     | 4.0     | 25W                | 3.8             | 1.4               | 200    | 50    | 2400K | 80  |  |
|  | LED4E12B1127K  | LED 4W DIMMABLE CANDELABRA BLUNT TIP - 2700K         | 120     | 4.0     | 25W                | 3.8             | 1.4               | 260    | 65    | 2700K | 80  |  |
|  | LED4E12B1150K  | LED 4W DIMMABLE CANDELABRA BLUNT TIP - 5000K         | 120     | 4.0     | 25W                | 3.8             | 1.4               | 280    | 70    | 5000K | 80  |  |
|  | LED4E26B1124K  | LED 4W DIMMABLE BLUNT TIP - 2400K                    | 120     | 4.0     | 25W                | 3.8             | 1.4               | 200    | 50    | 2400K | 80  |  |
| LED4E26B1127K  | LED 4W DIMMABLE BLUNT TIP - 2700K                    | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E12B1127KF   | LED 4W DIMMABLE CANDELABRA FROSTED BLUNT TIP - 2700K | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E26B1127KF   | LED 4W DIMMABLE FROSTED BLUNT TIP - 2700K            | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E12F1127K  | LED 4W DIMMABLE CANDELABRA FLAME TIP - 2700K         | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E26F1127K  | LED 4W DIMMABLE FLAME TIP - 2700K                    | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |
| LED4E26F1127KF   | LED 4W DIMMABLE FROSTED FLAME TIP - 2700K            | 120  | 4.0     | 25W     | 3.8                | 1.4             | 260               | 65     | 2700K | 80    |     |  |

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

# CREATING BEAUTY

TCP has a **20-year history in energy-efficient lighting.**

Thanks to our **cutting edge technology** and manufacturing

expertise, we have shipped billions of high quality lamps. Our

**integrated technology and manufacturing** provides

**expedited time-to-market.** With TCP, you can count on

unique lighting products designed to meet very specific needs—lighting that

transforms your surroundings and envelopes you in warmth—**lighting**

**that generates beauty** with every flip of the switch.

LED

For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit [tcp.com](http://tcp.com)

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516