



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## LMSW105W Scene Switch *Wattstopper*

Catalog Number	LMSW105W
Manufacturer	Wattstopper
Description	Digital Scene Switch, Wall Mount Type; 1.7 Inch W X 1.3 Inch D X 4.1 Inch H Size; White Color; UI, Cul Approval; 24 VDC Voltage Rating; 5 Button(S); Rohs Compliant; Current Rating 5 Milliampere; Indicator Type Led; Temperature Rating 32 to 131 Deg F
Weight per unit	2.9 (lbs/each)
Product Category	Lighting Controls

### Features

number of buttons	5 in
Voltage Rating	24 VDC

### Material, Color, and Finish

Color	White
-------	-------

### Dimensions and Weight

Size	1.7 Inch W x 1.3 Inch D x 4.1 Inch H
------	--------------------------------------

### Descriptions

Additional Information	RoHS Compliant; Current Rating 5 Milliampere; Indicator Type LED; Temperature Rating 32 to 131 Deg F
Commodity Description	LIGHTING CONTROLS
Description	SCENE SWITCH
extra long description	WALL MOUNT TYPE; 1.7 INCH W X 1.3 INCH D X 4.1 INCH H SIZE; WHITE COLOR; UL, CUL APPROVAL; 24 VDC VOLTAGE RATING; 5 BUTTON(S); ROHS COMPLIANT; CURRENT RATING 5 MILLIAMPERE; INDICATOR TYPE LED; TEMPERATURE RATING 32 TO 131 DEG F
Long Description	DIGITAL SCENE SWITCH, WALL MOUNT TYPE; 1.7 INCH W X 1.3 INCH D X 4.1 INCH H SIZE; WHITE COLOR; UL, CUL APPROVAL; 24 VDC VOLTAGE RATING; 5 BUTTON(S); ROHS COMPLIANT; CURRENT RATING 5 MILLIAMPERE; INDICATOR TYPE LED; TEMPERATURE RATING 32 TO 131 DEG F
Product Type	Digital Scene Switch

### Manufacturer Information

Brand	WATTSTOPPER
GTIN	00754182929283
Manufacturers Part Number	LMSW105W
UPC	754182929283



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Type	WALL MOUNT

## Packaging

Carton	10
Package	40
Weight Per each	2.9

## Uses, Certifications, and Standards

Approval	UL, CUL
----------	---------