

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## LPJ4SP 600V J TD Fuse Bussmann Fuses

Catalog Number	
Manufacturer	
Description	Eaton Bussmann Series Class J Fuse, LPJ, Time-Delay,
	Dual-Element Current Limiting Fuse, 4 A, Non-Idicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	
Product Category	Dual Element
Features	
amperage rating	4
connection	
dimensions	2.2500 IN X 0.8100 IN X 0.8100 IN
element	Dual
Fuse Class	Class J
interrupt rating	100 kAIC Vdc300 kAIC at 600 Vac
media	Yes
Response Time	10 sec at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 2.25 In Length
Descriptions	
Description	600V J TD FUSE
extra long description	BUSS LPJ-4SP LOW-PEAK CLASS J T/D
Features	Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element,
	time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while
	delivering a minimum of 10 seconds of 500 percent rated current ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu
Long Description	Eaton Bussmann Series Class J fuse, LPJ, time-delay, dual-element current limiting fuse, 4 A, non-idicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Class J T/D
Special Features	Non-indicating, High in-rush current motor protection



## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Eaton
GTIN	00051712522816
Manufacturers Part Number	LPJ4SP
UPC	051712522816
Taxonomies, Classifications, and Cat	tegories
Category Description	Euros & Euro Accossorios
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.101
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked,RoHS Compliant