

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## LT2UL 2" Ua Sealtite Conduit, Bonded UI 50'

Southwire Company	LT2UL	
Catalog Number Manufacturer	Southwire Company	
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound Strip Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is	
	Constructed With A Square Locked Steel Strip With An Integral Copperbonding Strip Enclosed Within The Steel Convolutions. For 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild	
Weight per unit Product Category	1.1 (lbs/each) Conduit & Raceways	
Features		
outside diameter	2357	
Dimensions and Weight		
Length	50	
Descriptions		
Description	2" UA SEALTITE CONDUIT, BONDED UL 50'	
extra long description	SWC 55093105 Titan2 Type UL Liquidt	
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized steel. For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked steel strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild	
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit	
Manufacturer Information		
Brand	Flexible Conduit	
GTIN	00032886042713	
	55093105	
UPC	032886042713	
Taxonomies, Classifications, and (	•	
Category Description		
Туре	LTM-UL	
Trade Size		
Trade Size		



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability	Inactivo	
	Indetive	
	50	