



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## LT350 3-1/2" LT STR Conn

*Crouse-Hinds*

Catalog Number	LT350
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, Straight, Non-Insulated, Malleable Iron, 3-1/2"
Weight per unit	6.4 (lbs/each)
Product Category	Liquid Tight Fittings

### Features

connection	Threaded
dimensions	3.8100 IN X 5.2500 IN X 5.2500 IN
installation type	THREADED

### Material, Color, and Finish

Color	MALLEABLE IRON
-------	----------------

### Descriptions

Description	3-1/2" LT STR CONN
extra long description	MIDWEST LT350 3 1/2 LT CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, Straight, Non-insulated, Malleable iron, 3-1/2"
Product Type	3 1/2 LT Conn

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564303509
Manufacturers Part Number	LT350
UPC	784564303509

### Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Type	Liquidtight connector

### Trade Size

Trade Size	3 1/2 in
------------	----------



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Weight Per each	6.35

## Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.2