

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

installation type THREADED





### LT35090 3-1/2" 90D LT Conn Crouse-Hinds

Catalog Number	LT35090
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 90° Angle, Non-Insulated, Malleable Iron, 3-1/2"
Weight per unit	-
	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	12.3800 IN X 5.2500 IN X 12.3800 IN

#### Material, Color, and Finish

-	
Color	MALLEABLE IRON

#### **Descriptions**

Description	3-1/2" 90D LT CONN
extra long description	MIDWEST LT35090 3 1/2 LT 90 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 90° angle, Non-insulated, Malleable iron, 3-1/2"
Product Type	3 1/2 LT 90 Degree Conn

#### **Manufacturer Information**

Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564903501
Manufacturers Part Number	LT35090
UPC	784564903501

#### Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Liquidtight connector

#### **Trade Size**

Trade Size 3 1/2 in	
---------------------	--



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	19.5
Uses, Certifications, and Standa	ards
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.45