

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LT3845 3/8" 45D LT Conn Crouse-Hinds

Catalog Number	LT3845
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC 45° Angle, Non-Insulated, Malleable Iron, 3/8"
Weight per unit	0.1800 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	2.4400 IN X 1.1300 IN X 1.1300 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions Description	3/8" 45D LT CONN
extra long description	MIDWEST LT3845 3/8 LT 45 DEGREE CON
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are
reatures	designed to protect conductors from mechanical damage due to
	vibration and movement while sealing out cutting oils, coolants,
	water, and dust. Typical applications include the wiring of
	machine tools, motors, transformers, food processing
	equipment, robotics, air conditioning units and illuminated signs.
	To meet any customer preference, Crouse-Hinds series
	liquidtight fittings are available in a variety sizes, configurations
	and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC,
	45° angle, Non-insulated, Malleable iron, 3/8"
Product Type	3/8 LT 45 Degree Conn
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00784564450388
Manufacturers Part Number	LT3845
UPC	784564450388
Taxonomies, Classifications, and	Categories
Category Description	
Туре	Liquidtight connector
Trade Size	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Package	25
Weight Per each	0.18

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.7