

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### LTB7545G 3/4" 45D LT Conn Crouse-Hinds

LTB7545G
Crouse-Hinds
Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC, 45° Angle, Aluminum Ground Lug, Insulated, #4-14 Awg Lug Size, Malleable Iron, 3/4"
0.5200 (lbs/each)
Liquid Tight Fittings
Threaded
2.6900 IN X 1.5600 IN X 2.6880 IN
THREADED

#### Material, Color, and Finish

Color	MALLEABLE IRON

#### **Descriptions**

Description	3/4" 45D LT CONN
extra long description	MIDWEST LTB7545G 3/4 LT 45 DEG CONN
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs. To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Insulated, #4-14 AWG lug size, Malleable iron, 3/4"
Product Type	3/4 LT 45 Deg Conn Ground Lug Insulated
Special Features	With 14 To 4 AWG Aluminum Grounding Lug

2/4" AED LT CONNI

#### **Manufacturer Information**

Brand	Eaton	
GTIN	00784564264220	
Manufacturers Part Number	LTB7545G	
UPC	784564264220	

### **Taxonomies, Classifications, and Categories**

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Liquidtight connector



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

<b>Trade Size</b> Trade Size	3/4 in
Packaging	4
Carton	1
Package	10
Weight Per each	0.52
<b>Uses, Certifications, and Standards</b>	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.86