



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)



## Eaton M22 Contact Block

**M22-K10**

**UPC:**786685278001

### Dimensions:

- **Height:** .25 IN
- **Length:** 1.25 IN
- **Width:** 1.18 IN

**Weight:**.04 LB

**Notes:**All NC contact blocks are positively driven contact.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Special Features:** NC contact blocks are positively driven
- **Type:** Contact Block
- **Actuator:** Front, Screw
- **Button Color:** Black
- **Contact Configuration:** NO
- **Environmental Rating:** IP66, NEMA 4X, 13
- **Size:** 22.5 mm
- **Series:** M22

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22-K 3D Model Xchange](#)
- [M22-K 3D Inventor](#)
- [M22-K 2D PDF](#)
- [M22-K 2D Drawing Xchange](#)
- [M22-K AutoCAD 2D Footprint](#)
- [M22-K AutoCAD 2D Footprint \(mm\)](#)

- [M22 Operators and Accessories](#)
- [M22 Pilot Devices](#)
- [Quick Selector - M22 Pushbuttons](#)
- [Global Data Sheet - M22-K10](#)

**Certifications:**

- CSA Certified
- CCC Marked
- Lloyd's Register Certified

**Product compliance:**

- CE Marked
- Bureau Veritas
- GoST-R



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)



## Eaton M22 Contact Block

**M22-K10**

**UPC:**786685278001

### Dimensions:

- **Height:** .25 IN
- **Length:** 1.25 IN
- **Width:** 1.18 IN

**Weight:**.04 LB

**Notes:**All NC contact blocks are positively driven contact.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Special Features:** NC contact blocks are positively driven
- **Type:** Contact Block
- **Actuator:** Front, Screw
- **Button Color:** Black
- **Contact Configuration:** NO
- **Environmental Rating:** IP66, NEMA 4X, 13
- **Size:** 22.5 mm
- **Series:** M22

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22-K 3D Model Xchange](#)
- [M22-K 3D Inventor](#)
- [M22-K 2D PDF](#)
- [M22-K 2D Drawing Xchange](#)
- [M22-K AutoCAD 2D Footprint](#)
- [M22-K AutoCAD 2D Footprint \(mm\)](#)

- [M22 Operators and Accessories](#)
- [M22 Pilot Devices](#)
- [Quick Selector - M22 Pushbuttons](#)
- [Global Data Sheet - M22-K10](#)

**Certifications:**

- CSA Certified
- CCC Marked
- Lloyd's Register Certified

**Product compliance:**

- CE Marked
- Bureau Veritas
- GoST-R