

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



NPP16DEFP Power/Relay Pack Occupancy Controlled Dimming Lithonia Lighting - Acuity

Catalog Number	NPP16DEFP
Manufacturer	Lithonia Lighting - Acuity
Description	The Nlight NPP16 Series Power Pack Provides System Power and Switches Lighting Loads With Optional 0-10VDC Dimming Output (Via Chase Nipple) For Commercial and Industrial Lighting Contro
Mainly and the	Applications
Weight per unit	0.8400 (lbs/each)
Product Category	Lighting Accessories
Features	
average life	Not Applicable
dimmable	Yes
Hardware	Yes
Lamp Included	Not Applicable
Material	Plastic
Maximum Operating Temperature	60
pallet quantity	100
Voltage Rating	120,277
Warranty	5
Material, Color, and Finish	
Color	White
Finish	Gloss
Dimensions and Weight	
Height	4
Length	4
Width	2.5
Descriptions	
Description	POWER/RELAY PACK OCCUPANCY CONTROLLED DIMMING
extra long description	LITH NPP16 D EFP Power/Relay Pack,
Features	Design Select
Long Description	The nLight nPP16 series power pack provides system power and switches lighting loads with optional 0-10VDC dimming output (via chase nipple) for commercial and industrial lighting control applications
Product Type	Power Pack



Weight

Weight Per each

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

0.84

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

$N/I \cap M \cap I$	CASTILLA	Information
11/1/41 11 11	141 III PI	
IVIGITAL	Ideldiei	

Brand	Nlight	
GTIN	00193047356800	
Manufacturers Part Number	NPP16 D EFP	
UPC	193047356800	

Taxonomies, Classifications, and Categories Category Description Com

Туре	POWER PACK	
Packaging		
Carton	1	

Commercial switches

Uses, Certifications, and Standards

Application	Education, Government, Healthcare, Hospitality, House of Worship, Manufacturing, Offices & Banks, Retail, Sports and Recreation, Warehouses
environmental conditions	Indoor
Mounting	Unit to J Box
standard	C-UL-US,ULCA Title 24,DLC Standard,ROHS