

# Rigid Metal Conduit, IMC or EMT “K-Clamps”

## Applications

- Designed to secure rigid metal conduit, IMC or EMT across, parallel or perpendicular to beam, channel and angle supports.

## Features




- Easily installs.
- Capable of withstanding heavy loads.

## Material/Finish

- Castings: malleable iron/hot dip galvanized
- Hardware: steel/mechanically galvanized

## Certifications and Compliances

- CSA Standard: C22.2 No. 18.4
- CSA Certified: 065178

|  | Catalog Number | Trade Size (Inches) | Weight Lbs./Kgs. Per 100 |
|--|----------------|---------------------|--------------------------|
| <b>Right Angle Type — Hot Dip/Mechanically Galvanized — For Rigid, IMC, EMT</b>                            |                |                     |                          |
|  <p>Right Angle Type</p> | PC-50RA        | 1/2                 | 37.00/16.78              |
|  | PC-75RA        | 3/4                 | 40.00/18.14              |
|  | PC-100RA       | 1                   | 42.00/19.05              |
|  | PC-125RA       | 1-1/4               | 49.00/22.23              |
|  | PC-150RA       | 1-1/2               | 54.00/24.49              |
|  | PC-200RA       | 2                   | 71.00/32.21              |
|  | PC-250RA       | 2-1/2               | 95.00/43.09              |
|  | PC-300RA       | 3                   | 107.00/48.53             |
|  | PC-350RA       | 3-1/2               | 120.00/54.43             |
|  | PC-400RA       | 4                   | 131.00/59.42             |
|  | PC-500RA †     | 5                   | 160.00/72.57             |
| PC-600RA †   | 6              | 195.00/88.45        |                          |
| <b>Parallel Type — Hot Dip/Mechanically Galvanized — For Rigid, IMC, EMT</b>                               |                |                     |                          |
|  <p>Parallel Type</p>   | PC-50PAR       | 1/2                 | 50.00/22.68              |
|  | PC-75PAR       | 3/4                 | 53.00/24.04              |
|  | PC-100PAR      | 1                   | 60.00/27.22              |
|  | PC-125PAR      | 1-1/4               | 70.00/31.75              |
|  | PC-150PAR      | 1-1/2               | 82.00/37.19              |
|  | PC-200PAR      | 2                   | 132.00/59.87             |
|  | PC-250PAR      | 2-1/2               | 192.00/87.09             |
|  | PC-300PAR      | 3                   | 194.00/88.00             |
|  | PC-350PAR      | 3-1/2               | 216.00/97.98             |
|  | PC-400PAR      | 4                   | 232.00/105.23            |
| <b>Edge Type — Hot Dip/Mechanically Galvanized — For Rigid Conduit Only</b>                                |                |                     |                          |
|  <p>Edge Type</p>       | PC-50ET        | 1/2                 | 63.00/28.58              |
|  | PC-75ET        | 3/4                 | 69.00/31.30              |
|  | PC-100ET       | 1                   | 82.00/37.19              |
|  | PC-125ET       | 1-1/4               | 95.00/43.09              |
|  | PC-150ET       | 1-1/2               | 108.00/49.00             |
|  | PC-200ET       | 2                   | 121.00/54.88             |
|  | PC-250ET       | 2-1/2               | 153.00/69.40             |
| PC-300ET   | 3              | 214.00/97.07        |                          |

† Not CSA Certified.

# Rigid Metal Conduit, IMC or EMT “K-Clamps”

## Applications

- Designed to secure rigid metal conduit, IMC or EMT across, parallel or perpendicular to beam, channel and angle supports.

## Features




- Easily installs.
- Capable of withstanding heavy loads.

## Material/Finish

- Castings: malleable iron/hot dip galvanized
- Hardware: steel/mechanically galvanized

## Certifications and Compliances

- CSA Standard: C22.2 No. 18.4
- CSA Certified: 065178

|  | Catalog Number | Trade Size (Inches) | Weight Lbs./Kgs. Per 100 |
|--|----------------|---------------------|--------------------------|
| <b>Right Angle Type — Hot Dip/Mechanically Galvanized — For Rigid, IMC, EMT</b>                            |                |                     |                          |
|  <p>Right Angle Type</p> | PC-50RA        | 1/2                 | 37.00/16.78              |
|  | PC-75RA        | 3/4                 | 40.00/18.14              |
|  | PC-100RA       | 1                   | 42.00/19.05              |
|  | PC-125RA       | 1-1/4               | 49.00/22.23              |
|  | PC-150RA       | 1-1/2               | 54.00/24.49              |
|  | PC-200RA       | 2                   | 71.00/32.21              |
|  | PC-250RA       | 2-1/2               | 95.00/43.09              |
|  | PC-300RA       | 3                   | 107.00/48.53             |
|  | PC-350RA       | 3-1/2               | 120.00/54.43             |
|  | PC-400RA       | 4                   | 131.00/59.42             |
|  | PC-500RA †     | 5                   | 160.00/72.57             |
| PC-600RA †   | 6              | 195.00/88.45        |                          |
| <b>Parallel Type — Hot Dip/Mechanically Galvanized — For Rigid, IMC, EMT</b>                               |                |                     |                          |
|  <p>Parallel Type</p>   | PC-50PAR       | 1/2                 | 50.00/22.68              |
|  | PC-75PAR       | 3/4                 | 53.00/24.04              |
|  | PC-100PAR      | 1                   | 60.00/27.22              |
|  | PC-125PAR      | 1-1/4               | 70.00/31.75              |
|  | PC-150PAR      | 1-1/2               | 82.00/37.19              |
|  | PC-200PAR      | 2                   | 132.00/59.87             |
|  | PC-250PAR      | 2-1/2               | 192.00/87.09             |
|  | PC-300PAR      | 3                   | 194.00/88.00             |
|  | PC-350PAR      | 3-1/2               | 216.00/97.98             |
| PC-400PAR  | 4              | 232.00/105.23       |                          |
| <b>Edge Type — Hot Dip/Mechanically Galvanized — For Rigid Conduit Only</b>                                |                |                     |                          |
|  <p>Edge Type</p>       | PC-50ET        | 1/2                 | 63.00/28.58              |
|  | PC-75ET        | 3/4                 | 69.00/31.30              |
|  | PC-100ET       | 1                   | 82.00/37.19              |
|  | PC-125ET       | 1-1/4               | 95.00/43.09              |
|  | PC-150ET       | 1-1/2               | 108.00/49.00             |
|  | PC-200ET       | 2                   | 121.00/54.88             |
|  | PC-250ET       | 2-1/2               | 153.00/69.40             |
| PC-300ET   | 3              | 214.00/97.07        |                          |

† Not CSA Certified.