

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PLG50R 1/2" Recessed Plug Appleton/Oz Gedney

Catalog Number	PLG50R
Manufacturer	Appleton/Oz Gedney
Description	Appleton Unilets Recessed Head Close-Up Plug, Size: 1/2 In, Material: Steel, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I, Groups A, B, C, D, Class Ii, Groups E, F, G, and Class Iii, For Use With Threaded Rigid Metal Conduit and Imc
Weight per unit	0.0500 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.
Features	
connection	Tapered MNPT
Material	Steel
Material, Color, and Finish	
Finish	Zinc Electroplate
Dimensions and Weight	
Size	1/2
Descriptions	
Description	1/2" RECESSED PLUG
extra long description	APP PLG-50R PLUG 1/2 REC HEAD CLOSE
Long Description	Appleton UNILETS Recessed Head Close-Up Plug, Size: 1/2 IN, Material: Steel, Finish: Zinc Electroplate, Connection: Tapered MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Groups A B, C, D, Class II, Groups E, F, G, And Class III, For Use With Threaded Rigid Metal Conduit And IMC
Product Type	Plug 1/2 Rec Head Close-Up-STL
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Explosionproof, dust-ignitionproof;Smooth, rounded integral bushing in each hub protects conductor insulation
Manufacturer Information	
Brand	Appleton
GTIN	00781381455541
Manufacturers Part Number	PLG-50R
UPC	781381455541



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Туре	Recessed Head Close-Up Plug
Packaging	
Carton	50
Package	500
Weight Per each	0.05
Uses, Certifications, and Standards	
Application	For Use With Threaded Rigid Metal Conduit and IMC
standard	And Class III;Class II, Groups E, F, G;UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Groups A, B, C, D