

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PLT2MIM0 8" 18LB BLK CBL Tie Panduit Corporation

Catalog Number	PLT2MM0	
Manufacturer	Panduit Corporation	
Description	Panduit PLT2M-M0 Locking Cable Ties Are Designed to Satisfy The Needs Of General Applications, While Delivering Consistent Performance and Reliability. Featuring A Curved Tip to Allow For Easy Pick Up From Flat Surfaces and Faster Initial Threading. Miniature Cross Section, 8.0" (203MM) Length. For Indoor/Outdoor Use, Made Of Weather Resistant Nylon 6.6, Are Black In Color and Come In Packages Of 1000.	
Weight per unit	1.4 (lbs/each)	
Product Category	Cable Ties & Wraps	
Features		
media	Yes	
Tensile Strength	18	
Dimensions and Weight		
Length	8	
Thickness	0.05	
Descriptions		
Description	8" 18LB BLK CBL TIE	
extra long description	PAN PLT2M-M0 Pan-Ty® PLT2M-M0 Cable	
Long Description	Panduit PLT2M-M0 Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Miniature cross section, 8.0" (203mm) length. For Indoor/Outdoor use, made of Weather Resistant Nylon 6.6, are black in color and come in packages of 1000.	
Product Type	Pan-Ty® PLT2M-M0 Cable Tie, Black, Uv PA6.6, 8"L, 18LB, PK10	
Special Features	Indoor/Outdoor	
Manufacturer Information	PANDUIT	

Brand	PANDUIT
GTIN	00074983540273
Manufacturers Part Number	PLT2M-M0
UPC	074983540273

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	Premium Cable Tie



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1000	
Package	5000	
Weight Per each	1.4	

Uses, Certifications, and Standards

standard

CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant