ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

PRHELB2X90 2" 90D STANDARD ELBOW

ROBROY/PLASTI-BOND

Catalog Number	PRHELB2X90
Manufacturer	ROBROY/PLASTI-BOND
Description	2X90 STANDARD ELBOW
Weight per unit	6.9 (lbs/each)
Product Category	Steel

Features

Bend Angle	90 Degree
Bend Radius	9.5 INCH
End Type	EXTERNAL THREADED
Material	Steel

Material, Color, and Finish

Finish	2 Mil Red Urethane Coated Interior, 40 Mil Gray PVC Coated Exterior

Descriptions

Additional Information	Diameter 2.083 Inch (Internal) x 2.455 Inch (External); Threaded Protector Cap Color Blue
Commodity Description	ELBOWS-COUPLINGS-NIPPLES - STEEL
Description	2" 90D STANDARD ELBOW
Long Description	2X90 STANDARD ELBOW ELBOW, STANDARD RADIUS TYPE; STEEL MATERIAL; 2 MIL RED URETHANE COATED INTERIOR, 40 MIL GRAY PVC COATED EXTERIOR FINISH; UL 6, UL (CANADA AND US), CSA C22.2, ETL APPROVAL; 10 STANDARD PACKAGE; 2 INCH TRADE SIZE; EXTERNAL THREADED END TYPE
Product Type	Elbow
Extra Long Description	STANDARD RADIUS TYPE; STEEL MATERIAL; 2 MIL RED URETHANE (INTERIOR AND THREAD)/40 MIL GRAY PVC (EXTERIOR) FINISH; UL (CANADA AND US), UL 6, CSA C22.2 APPROVAL; ISO 9001 APPLICABLE STANDARD; 10 PER PACK STANDARD PACKAGE; 2 INCH TRADE SIZE; EXTERNAL THREADED END TYPE; 90 DEGREE BEND ANGLE; 9.5 INCH BEND RADIUS; NIPPLE LENGTH 22-1/2 INCH; THREAD PROTECTOR COLOR BLUE; PRHELB MODEL

Manufacturer Information

Brand	PLASTIBOND REDH2OT[R] PLASTI-BOND
GTIN	00784011200368
Manufacturers Part Number	PRHELB-2X90
Model	Series PRHELB
UPC	889953

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Taxonomies, Classifications, and Categories

Category Description	ALL PLASTIBOND FITTINGS
Type	STANDARD RADIUS

Trade Size

Trade Size	2 INCH

Availability

Manufacturer Status	Non-Stock

Packaging

Carton	1
Package	10
Standard Package	10
Weight Per Each	6.9 (lbs/each)

Uses, Certifications, and Standards

Approval	UL 6, UL (Canada and US), CSA C22.2, ETL