

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PSDS60AXSR 60A 600V SS Sloperoof N/F Safety Switch W/Aux Pass & Seymour/Legrand

Catalog Number	PSDS60AXSR	
Manufacturer	Pass & Seymour/Legrand	
Description	60 Amps Sloped-Roof Stainless Steel Safety Switch With Auxiliary Contact.Legrands 316-Grade Sloped-Roof Stainless Steel Safety Switches Are Designed to Provide Superior Corrosion Resistance In Harsh Environments Like Food and Beverage Processing Plants Where Wash Down/Hose Down At Extreme Temperatures Is A Daily Necessity, As Well As Environments Where Salts, Acids, and Chemicals Are Prevalent. Legrands Sloped-Roof Stainless Steel Safety Switches With Nema 4X/12, IP66, 67, and 69K Ratings Are The Best Solu	
Weight per unit	13.0 (lbs/each)	
Product Category	Non-Fusible Heavy Duty Safety	
Features	#14 #10 A	
Wire Size	#14 - #10 Awg	
Descriptions		
Description	60A 600V SS SLOPEROOF N/F SAFETY SWITCH W/AUX	
extra long description	P&S PSDS60AXSR 60A 600V SS SLOPEROO	
Long Description	60 Amps Sloped-Roof Stainless Steel Safety Switch with Auxiliary Contact.Legrands 316-Grade Sloped-Roof Stainless Steel Safety Switches are designed to provide superior corrosion resistance in harsh environments like food and beverage processing plants where wash down/hose down at extreme temperatures is a daily necessity, as well as environments where salts, acids, and chemicals are prevalent. Legrands Sloped-Roof Stainless Steel Safety Switches with NEMA 4X/12, IP66, 67, and 69K ratings are the best solu	
Product Type	60A 600V SS Sloperoof Non-Fus Safesw Ax	
Manufacturer Information		
Brand	LEGRAND-PASS & SEYMOUR	
GTIN	00785007133653	
Manufacturers Part Number	PSDS60AXSR	
UPC	785007133653	
Taxonomies, Classifications, and G	Categories	
Туре		
Trade Size		
Amperage	60.0	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging		
Carton	1	
Weight Per each	13.04	
Uses, Certifications, and Stand	ards	
standard	cULus	