

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# PT2097HGRED Self Test Plugtail Gfci Recp Hosp GRD 20A RD Pass & Seymour/Legrand

Catalog Number	PT2097HGRED	
Manufacturer	Pass & Seymour/Legrand	
Description	20A 125V Plugtail Self Test Hospital Grade Gfci Red	
Weight per unit	0.2450 (lbs/each)	
Product Category	Gen Purpose Recept & Surge Pro	

#### **Features**

actuator	Control Circuit
amperage rating	20
connection	Built-in Connector
interrupt rating	4 to 6 mA
Material	Thermoplatic
media	Yes
Poles	2
trip range	4 to 6 mA
Trip Type	.025 Second Nominal
Voltage Rating	125

#### **Dimensions and Weight**

Height	4.2
Longth	1.03
Width	1.73

### **Descriptions**

•	
Description	SELF TEST PLUGTAIL GFCI RECP HOSP GRD 20A RD
extra long description	P&S PT2097HGRED SELF TEST PTAIL GFC
Long Description	20A 125V Plugtail Self Test Hospital Grade GFCI Red
Product Type	Self Test Ptail Gfci HG Rec 20A Red
Special Features	Pass & Seymour invented the GFCI receptacle, and at Legrand, we're constantly reinventing it to ensure the highest level of safety possible. From the most advanced self-testing device to audible alarms to nightlight combos, we're continuously resetting the bar on GFCI innovation and safety.

#### **Manufacturer Information**

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007048919
Manufacturers Part Number	PT2097-HGRED
UPC	785007048919



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies.	Classifications	and Categories
	0.000000	, a.i.a. categoiles

Category Description	Residential Switches
Type	PLUGTAIL® Hospital Grade Tamper-Resistant 20A Self-Test GFCI
	Receptacle
ekaning	

## **Packaging**

magnig		
Carton	1	
Package	10	
Weight Per each		

## Uses, Certifications, and Standards

Application	Commercial/Residential
environmental conditions	95% Humidity, UL 94 V2
Frequency Rating	60 Hz
Operating Temperature	-35°C to +66°C
standard	cULus, UL Listed, FSUL