

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PT350 350MCM Pin Term

Nsi Industries

Nsi Industries	
Catalog Number	PT350
Manufacturer	Nsi Industries
Description	Stranded Bi-Metallic Pin Terminal 350 MCM Stranded Bi-Metallic Pin Terminals Is Designed to Facilitate Termination Of Aluminum Conductors. Tin-Plated Stranded Copper Pin. Connector Bores Are Coated With Oxide Inhibitor. Supplied With Epdm Insulating Cover. UI 486B Listed. Rated 600 Volts.
Weight per unit	
Product Category	
Features	
connection	4/0 Pin
insulation	Diactical Cover
Material	Aluminum Tin Plated Conner Din
Number of Conductors	• •
Poles	1
Voltage Rating	600 V
Warranty	
Material, Color, and Finish	
Color	Brown
Finish	A lumping upp
Dimensions and Weight	
Size	L=4.08 - OD=1.15 - ID=.700 - Pin Dia=.496
Descriptions	
Description	350MCM PIN TERM
extra long description	NSI PT350 Aluminum Pin Terminal Cu
Features	Stranded Bi-Metallic Pin Terminal 350 MCM Stranded Bi-Metallic
reatures	Pin Terminals is designed to facilitate termination of aluminum
	conductors. Tin-plated stranded copper pin. Connector bores are
	coated with oxide inhibitor. Supplied with EPDM insulating cover.
	UL 486B listed. Rated 600 volts.
Long Description	Stranded Bi-Metallic Pin Terminal 350 MCM Stranded Bi-Metallic
	Pin Terminals is designed to facilitate termination of aluminum
	conductors. Tin-plated stranded copper pin. Connector bores are
	coated with oxide inhibitor. Supplied with EPDM insulating cover.
Due door Town	UL 486B listed. Rated 600 volts.
Product Type	Aluminum Pin Terminal Cu Pin 350 MCM
Special Features	350 MCM (STR) - 4/0 CU Pin Size



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Inf	tormation

Brand	NSi	
GTIN	00662381033109	
Manufacturers Part Number	PT350	
UPC	662381033109	

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Туре	Bi-Metallic Pin

Packaging

···-g···g		
Carton	1	
Weight Per each	0.45	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B
Temperature Rating	90 C