



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## PT4 Pin Terinals *Nsi Industries*

Catalog Number	PT4
Manufacturer	Nsi Industries
Description	Stranded Bi-Metallic Pin Terminal 4 Awg Stranded Bi-Metallic Pin Terminals Is Designed to Facilitate Termination Of Aluminum Conductors. Tin-Plated Stranded Copper Pin. Connector Bores Are Coated With Oxide Inhibitor. Supplied With Epdm Insulating Cover. Ul 486B Listed. Rated 600 Volts.
Weight per unit	0.0800 (lbs/each)
Product Category	Large Terminals & Connectors

### Features

connection	# 6 Pin
insulation	Plastisol Cover
Material	Aluminum - Tin Plated Copper Pin
Number of Conductors	1
Poles	1
Voltage Rating	600 V

### Material, Color, and Finish

Color	Tan
Finish	Aluminum

### Dimensions and Weight

Size	L=2.45 - OD=.630 - ID=.236 - Pin Dia=.188
------	---

### Descriptions

Description	PIN TERINALS
extra long description	NSI PT4 Aluminum Pin Terminal Cu Pi
Features	Stranded Bi-Metallic Pin Terminal 4 AWG Stranded Bi-Metallic Pin Terminals is designed to facilitate termination of aluminum conductors. Tin-plated stranded copper pin. Connector bores are coated with oxide inhibitor. Supplied with EPDM insulating cover. UL 486B listed. Rated 600 volts.
Long Description	Stranded Bi-Metallic Pin Terminal 4 AWG Stranded Bi-Metallic Pin Terminals is designed to facilitate termination of aluminum conductors. Tin-plated stranded copper pin. Connector bores are coated with oxide inhibitor. Supplied with EPDM insulating cover. UL 486B listed. Rated 600 volts.
Product Type	Aluminum Pin Terminal Cu Pin 4 Awg
Special Features	# 4 AWG (STR) - # 6 CU Pin Size



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	NSi
GTIN	00662381033017
UPC	662381033017

## Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Type	Bi-Metallic Pin

## Packaging

Carton	1
Weight Per each	0.08

## Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C