

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PTS750 Aluminum, Tin Plated Pin Terminal, 750 MCM Wire Si Nsi Industries

•
PTS750
Nsi Industries
Solid Pin Terminal For Copper and Aluminum Conductors 750 MCM All-Aluminum Pin Terminals Is Designed For Termination Of Both Aluminum and Copper Conductors. The Solid Pin Is Made Of Aluminum and Is Tin-Plated and Pre-Filled With Oxide Inhibitor. A Cover Is Provided For Quick Installation. Rated 600 Volts.
0.3800 (lbs/each)
Large Terminals & Connectors
500 Pin
Plastisol Cover
Aluminum
1
1
600 V
1 YEAR
Yellow
Tin Plated
L=3.79 - OD=1.46 - ID=1.02 - Pin Dia=.810
ALUMINUM, TIN PLATED PIN TERMINAL, 750 MCM WIRE SI
NSI PTS750 Aluminum Pin Terminal Al
Solid Pin Terminal for Copper and Aluminum Conductors 750 MCM All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Solid Pin Terminal for Copper and Aluminum Conductors 750 MCM All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Aluminum Pin Terminal Al Pin 750 MCM
750 MCM (STR) - 500 Pin Size



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				.					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	7
	v			u	а	L.I	uı	C-1	'In	H V	,, ,	па		u	

Brand	NSi	
GTIN	00662381033642	
Manufacturers Part Number	PTS750	
UPC	662381033642	

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Туре	Solid Pin

Packaging

Carton	3	
Weight Per each	0.38	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C