

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



QBHGFT2020 2P 20A 22KA Bolt-On Ground Fault W/PCB Self Test *Eaton Corp*

Catalog Number	QBHGFT2020			
Manufacturer	Eaton Corp			
Description	Eaton QB Gfci Circuit Breaker, Ground Fault Circuit Breaker, 20A,			
	22 Kaic, Two-Pole, 120/240V, QBHGF			
Weight per unit	0.8000 (lbs/each)			
Product Category	On Circuit Breakers			
Features				
dimensions	4.5000 IN X 2.7500 IN X 2.0000 IN			
interrupt rating	22			
Poles	2			
Voltage Rating	120/240 V			
Descriptions				
Description	2P 20A 22KA BOLT-ON GROUND FAULT W/PCB SELF TEST			
extra long description	ETN QBHGFT2020 2P 20A 22KA BOLT-ON			
Features	Eaton has a wide selection of UL rated miniature circuit breakers			
	for loadcenters, fuseboxes, or similar devices. Each pole provides			
	steel frame calibration and arc chutes with 5 - 100A continuous			
	in one-, two-, and three-pole designs. A full-range of accessories			
	expand customization options, including various mounting and			
	ring tung termination options.			
Long Description	Eaton QB GFCI circuit breaker, Ground fault circuit			
	breaker,20A,22 kAIC,Two-pole,120/240V,QBHGF			
Product Type	2P 20A 22KA Bolt-On Ground Fault W/PCB			
Manufacturer Information				
Brand	Eaton			
GTIN	00786676027823			
Manufacturers Part Number	QBHGFT2020			
UPC	786676027823			
Taxonomies, Classifications, and (Categories			
Туре	CCCI aircuit brookers			
Packaging				
Carton	1			
Weight Per each	0.8			
aroigna i oi odoli	V.IX			

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

U	ses,	Cer	tifica	tions,	and	Stand	ards
---	------	-----	--------	--------	-----	-------	------

	andards
Application	Marine Vessels and Equipment - Marine Vessels and Equipment -
	OtherOtherGeneration - Renewable Energy - Alternative
	EnergyGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper Converged
standard	UL 489