



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



R2210V 22-18 Nylon Ring #10 Stud

Nsi Industries

| | |
|------------------|---|
| Catalog Number | R2210V |
| Manufacturer | Nsi Industries |
| Description | 22-18 Awg Vinyl Insulated Ring #10 Stud, 100 Per Pack |
| Weight per unit | 0.1700 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|---------------------|------------------|
| Material | Vinyl Insulation |
| Number of Terminals | 1 |
| Terminal Size | # 10 |
| Voltage Rating | 300 V |
| Wire Size | 22-18 AWG |

Material, Color, and Finish

| | |
|-------|-----|
| Color | Red |
|-------|-----|

Descriptions

| | |
|------------------------|---|
| Description | 22-18 NYLON RING #10 STUD |
| extra long description | NSI R22-10V 22-18 Nylon Ring 1/4 St |
| Features | 22-18 AWG Vinyl Insulated Ring #10 Stud, 100 Per Pack |
| Long Description | 22-18 AWG Vinyl Insulated Ring #10 Stud, 100 Per Pack |
| Product Type | 22-18 Nylon Ring 1/4 Stud-Bulk |
| Special Features | Vinyl Insulated Ring Terminal 22-18 AWG - 100 Pack |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00662381067166 |
| Manufacturers Part Number | R22-10V |
| UPC | 662381067166 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------|
| Category Description | TERMINALS |
| Type | Vinyl Insulated Ring Terminal |

Availability

| | |
|-------------|-----|
| minimum qty | 100 |
|-------------|-----|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 100 |
| Weight Per each | 0.17 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

| | |
|--------------------------------|------------------------|
| Application | Wire Termination |
| environmental conditions | 75 C |
| standard | cULus |