



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## RB10050A 1" X 1/2" Reducing Bushing Alu

*Appleton/Oz Gedney*

Catalog Number	RB10050A
Manufacturer	Appleton/Oz Gedney
Description	Reducing Bushing, Size: 1 X 1/2 In, Material: Aluminum, Finish: Natural, Connection: NPT, Standard: Class I: Groups A, B, C, D, Class Ii: Groups E, F, G, Class Iii, UI 886 (1203), UI E10444, Csa C22.2 No. 25, C22.2 No. 30, Csa 065181, F
Weight per unit	0.0500 (lbs/each)
Product Category	Aluminum

### Features

connection	NPT
Material	Aluminum

### Material, Color, and Finish

Finish	Unfinished
--------	------------

### Dimensions and Weight

Size	1 X 1/2
------	---------

### Descriptions

Description	1" X 1/2" REDUCING BUSHING ALU
extra long description	APP RB100-50A RDC BUSH ALUM 1 TO 1/
Long Description	Reducing Bushing, Size: 1 X 1/2 IN, Material: Aluminum, Finish: Natural, Connection: NPT, Standard: Class I: Groups A, B, C, D, Class II: Groups E, F, G, Class III, UL 886 (1203), UL E10444, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181, F
Product Type	RDC Bush Alum 1 to 1/2 In NPT
Special Features	Smooth rounded integral bushing protects conductor insulation

### Manufacturer Information

Brand	Appleton
GTIN	00781381321075
Manufacturers Part Number	RB100-50A
UPC	781381321075

### Taxonomies, Classifications, and Categories

Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Type	Reducing Bushing

### Packaging

Carton	25
Package	100
Weight Per each	0.05



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application

For Reducing Conduit Entries To A Smaller Size In Threaded Rigid  
And IMC Conduit Systems

standard

Class I: Groups A, B, C, D, Class II: Groups E, F, G, Class III, UL 886  
(1203), UL E10444, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181