# **Specifications**



### Photo is representative



## Eaton RES-10

Eaton Bussmann series RES fuse, time lag, non current-limiting, Industrial and commercial structures, 10 A, Class H, Nonindicating, Ferrule end x ferrule end, 10 kAIC at 250 Vac, Standard, 10, 600 V

General specifications	
PRODUCT NAME	Eaton Bussmann series RES fuse
CATALOG NUMBER	RES-10
UPC	051712110105
PRODUCT LENGTH/DEPTH	5 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable



Electrical rating	
AMPERAGE RATING	10 A
INTERRUPT RATING	10 kAIC at 250 Vac
VOLTAGE RATING	600 V

Physical details	
PACKAGING TYPE	Standard
PACKAGING TYPE	Standard

General information	
CLASS	Class H
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
QUANTITY	10
SPECIAL FEATURES	Super lag, time lag, non current-limiting

Resources	
CATALOGS	Bussmann series complete full line catalog no. 1007
	<u>RES-10~SUPER LAG</u> <u>RENEWABLE FUSE 10/600</u>
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RES-10

### **PROJECT NAME:**

**PROJECT NUMBER:** 

### PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights

Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



# **Specifications**



### Photo is representative



## Eaton RES-10

Eaton Bussmann series RES fuse, time lag, non current-limiting, Industrial and commercial structures, 10 A, Class H, Nonindicating, Ferrule end x ferrule end, 10 kAIC at 250 Vac, Standard, 10, 600 V

General specifications	
PRODUCT NAME	Eaton Bussmann series RES fuse
CATALOG NUMBER	RES-10
UPC	051712110105
PRODUCT LENGTH/DEPTH	5 in
PRODUCT HEIGHT	0.81 in
PRODUCT WIDTH	0.81 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable



Electrical rating	
AMPERAGE RATING	10 A
INTERRUPT RATING	10 kAIC at 250 Vac
VOLTAGE RATING	600 V

Physical details	
PACKAGING TYPE	Standard
PACKAGING TYPE	Standard

General information	
CLASS	Class H
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
QUANTITY	10
SPECIAL FEATURES	Super lag, time lag, non current-limiting

Resources	
CATALOGS	Bussmann series complete full line catalog no. 1007
	<u>RES-10~SUPER LAG</u> <u>RENEWABLE FUSE 10/600</u>
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RES-10

### **PROJECT NAME:**

**PROJECT NUMBER:** 

### PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights

Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

