

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Category Description

Type

RF9540NDLA Dim Aspirerf Deco MSTR All-Load Neut La *Eaton Wiring Devices*

Catalog Number	RF9540NDLA
Manufacturer	Eaton Wiring Devices
Description	Eaton Z-Wave Dimmer Switch, Light Almond, Single Pole, 120 Vac, 300W Dimmable Led/CFL, 600W Incandescent, Halogen, Magnetic Low Voltage, Electronic Low Voltage, Dimmer Switch, Multi-Location, 32°F to 104°F (0°C to 40°C) 739033
Weight per unit	0.3700 (lbs/each)
Product Category	Lighting Dimmers
atures	
dimensions	1.3600 IN X 1.5000 IN X 3.8100 IN
media	Yes
Voltage Rating	120 V
Wattage	300 W (LED, CFL), 600 W (INC/HAL, ELV, MLV)
scriptions	
- Description	DIM ASPIRERF DECO MSTR ALL-LOAD NEUT LA
extra long description	EWD RF9540-NDLA Dim AspireRF Deco M
Features	Add wireless control to your lighting with Eaton's Z-Wave wireless collection to make your home connected and smart. T complete offering of lighting controls is easy to install, requires no special wiring and is perfect for both existing homes and ne construction. With Z-Wave based technology you can create your wireless home network to enhance security, control appliances, set the right mood and save energy. Select from a range of styles and colors to match your home's decor.
Long Description	Eaton Z-Wave dimmer switch, Light Almond, Single pole, 120 V 300W Dimmable LED/CFL, 600W Incandescent, Halogen, Magnetic Low Voltage, Electronic Low Voltage, Dimmer switch Multi-location, 32°F to 104°F (0°C to 40°C) 739033
Product Type	Dim Aspirerf Deco MSTR All-Load Neut La
Special Features	RF Controls Dimmers
nufacturer Information	
Brand	Eaton
GTIN	00032664739033
Manufacturers Part Number	RF9540-NDLA
UPC	032664739033

Dimmer switch

Residential dimmers, motion sensors, controls, & photo cells



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status	Inactive
Packaging Carton	1
Doolsono	6
Weight Per each	0.37
Uses, Certifications, and Standards	
Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities - Other
Operating Temperature	32 to 104 °F (0 to 40 °C)
standard	NOM,cULus Listed