

Reducing Washers

Type RW

Use:

To reduce a knockout or sliphole in a sheet metal enclosure to a smaller trade size.

Material/Finish:

Steel/Zinc Pre-Galvanized

Third Party Certification:



UL Listed: E11857



CSA Certified: 057250

Applicable Third Party Standards:

UL Standard: 514B

CSA Standard: C22.2 No. 18


NEMA: FB-1

Note:


Two reducing washers are required for each knockout.

| Trade Size (inches) | Catalog Number | Dimensions in Inches | |
|------------------------|-------------------|----------------------|------|
| | | A | B |
| 3/4 x 1/2 | RW-2S | 0.88 | 1.44 |
| 1 x 1/2 | RW-3S | 0.88 | 1.75 |
| 1 x 3/4 | RW-4S | 1.11 | 1.75 |
| 1 1/4 x 1/2 | RW-5S | 0.88 | 2.19 |
| 1 1/4 x 3/4 | RW-6S | 1.11 | 2.19 |
| 1 1/4 x 1 | RW-7S | 1.37 | 2.19 |
| 1 1/2 x 1/2 | RW-8S | 0.88 | 2.50 |
| 1 1/2 x 3/4 | RW-9S | 1.11 | 2.50 |
| 1 1/2 x 1 | RW-10S | 1.37 | 2.50 |
| 1 1/2 x 1 1/4 | RW-11S | 1.73 | 2.50 |
| 2 x 1/2 | RW-12S | 0.88 | 3.00 |
| 2 x 3/4 | RW-13S | 1.11 | 3.00 |
| 2 x 1 | RW-14S | 1.37 | 3.00 |
| 2 x 1 1/4 | RW-15S | 1.73 | 3.00 |
| 2 x 1 1/2 | RW-16S | 1.98 | 3.00 |
| 2 1/2 x 1/2 | RW-17S | 0.88 | 3.50 |
| 2 1/2 x 3/4 | RW-18S | 1.11 | 3.50 |
| 2 1/2 x 1 | RW-19S | 1.37 | 3.50 |
| 2 1/2 x 1 1/4 | RW-20S | 1.73 | 3.50 |
| 2 1/2 x 1 1/2 | RW-21S | 1.98 | 3.50 |
| 2 1/2 x 2 | RW-22S | 2.45 | 3.50 |
| 3 x 1 | RW-25S | 1.37 | 4.13 |
| 3 x 1 1/4 | RW-26S | 1.73 | 4.13 |
| 3 x 1 1/2 | RW-27S | 1.98 | 4.13 |
| 3 x 2 | RW-28S | 2.45 | 4.13 |
| 3 x 2 1/2 | RW-29S | 2.97 | 4.13 |
| 3 1/2 x 1 1/2 | RW-34S• | 1.98 | 4.63 |
| 3 1/2 x 2 | RW-35S• | 2.45 | 4.63 |
| 3 1/2 x 2 1/2 | RW-36S• | 2.97 | 4.63 |
| 3 1/2 x 3 | RW-37S• | 3.59 | 4.63 |
| 4 x 2 | RW-43S• | 2.50 | 5.15 |
| 4 x 2 1/2 | RW-44S• | 2.97 | 5.15 |
| 4 x 3 | RW-45S• | 3.59 | 5.15 |
| 4 x 3 1/2 | RW-46S• | 4.13 | 5.15 |

•Not CSA Certified.



Type RW



Reducing Washers

Type RW

Use:

To reduce a knockout or sliphole in a sheet metal enclosure to a smaller trade size.

Material/Finish:

Steel/Zinc Pre-Galvanized

Third Party Certification:



UL Listed: E11857



CSA Certified: 057250

Applicable Third Party Standards:

UL Standard: 514B

CSA Standard: C22.2 No. 18


NEMA: FB-1

Note:

Two reducing washers are required for each knockout.

| Trade Size (inches) | Catalog Number | Dimensions in Inches | |
|------------------------|-------------------|----------------------|------|
| | | A | B |
| 3/4 x 1/2 | RW-2S | 0.88 | 1.44 |
| 1 x 1/2 | RW-3S | 0.88 | 1.75 |
| 1 x 3/4 | RW-4S | 1.11 | 1.75 |
| 1 1/4 x 1/2 | RW-5S | 0.88 | 2.19 |
| 1 1/4 x 3/4 | RW-6S | 1.11 | 2.19 |
| 1 1/4 x 1 | RW-7S | 1.37 | 2.19 |
| 1 1/2 x 1/2 | RW-8S | 0.88 | 2.50 |
| 1 1/2 x 3/4 | RW-9S | 1.11 | 2.50 |
| 1 1/2 x 1 | RW-10S | 1.37 | 2.50 |
| 1 1/2 x 1 1/4 | RW-11S | 1.73 | 2.50 |
| 2 x 1/2 | RW-12S | 0.88 | 3.00 |
| 2 x 3/4 | RW-13S | 1.11 | 3.00 |
| 2 x 1 | RW-14S | 1.37 | 3.00 |
| 2 x 1 1/4 | RW-15S | 1.73 | 3.00 |
| 2 x 1 1/2 | RW-16S | 1.98 | 3.00 |
| 2 1/2 x 1/2 | RW-17S | 0.88 | 3.50 |
| 2 1/2 x 3/4 | RW-18S | 1.11 | 3.50 |
| 2 1/2 x 1 | RW-19S | 1.37 | 3.50 |
| 2 1/2 x 1 1/4 | RW-20S | 1.73 | 3.50 |
| 2 1/2 x 1 1/2 | RW-21S | 1.98 | 3.50 |
| 2 1/2 x 2 | RW-22S | 2.45 | 3.50 |
| 3 x 1 | RW-25S | 1.37 | 4.13 |
| 3 x 1 1/4 | RW-26S | 1.73 | 4.13 |
| 3 x 1 1/2 | RW-27S | 1.98 | 4.13 |
| 3 x 2 | RW-28S | 2.45 | 4.13 |
| 3 x 2 1/2 | RW-29S | 2.97 | 4.13 |
| 3 1/2 x 1 1/2 | RW-34S• | 1.98 | 4.63 |
| 3 1/2 x 2 | RW-35S• | 2.45 | 4.63 |
| 3 1/2 x 2 1/2 | RW-36S• | 2.97 | 4.63 |
| 3 1/2 x 3 | RW-37S• | 3.59 | 4.63 |
| 4 x 2 | RW-43S• | 2.50 | 5.15 |
| 4 x 2 1/2 | RW-44S• | 2.97 | 5.15 |
| 4 x 3 | RW-45S• | 3.59 | 5.15 |
| 4 x 3 1/2 | RW-46S• | 4.13 | 5.15 |

•Not CSA Certified.



Type RW

