

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **\$128V 12-10AWG #8 STD Vinyl Spade** *Nsi Industries*

Catalog Number	S128V
Manufacturer	Nsi Industries
Description	Spade Terminal, Vinyl Insulated, 12-8 Wire Range, #8 Stud Size,
	Electro Tin Plated Copper With Brazed Seam, Culus Listed.
	Provides Safe and Reliable Connection Because It Cannot Be
	Disconnected Unless The Screw Is Completely Removed,
	Measures 0.812 Long By 0.375 Wide.
Weight per unit	0.2040 (lbs/each)
Product Category	Small Terminals & Connectors

#### **Features**

Vinyl Insulation
1
# 8
300 V
12-10 AWG

#### Material, Color, and Finish

Color Yellow
--------------

#### **Descriptions**

Description	12-10AWG #8 STD VINYL SPADE
extra long description	NSI S12-8V 16-14 Bare Locking Spade
Features	Spade terminal, vinyl insulated, 12-8 wire range, #8 stud size, electro tin plated copper with brazed seam, cULus listed. Provides safe and reliable connection because it cannot be disconnected unless the screw is completely removed, measures 0.812 long by 0.375 wide.
Long Description	Spade terminal, vinyl insulated, 12-8 wire range, #8 stud size, electro tin plated copper with brazed seam, cULus listed. Provides safe and reliable connection because it cannot be disconnected unless the screw is completely removed, measures 0.812 long by 0.375 wide.
Product Type	16-14 Bare Locking Spade # 10 Stud
Special Features	Vinyl Insulated Spade Terminal 12-10 AWG - 50 Pack

#### **Manufacturer Information**

Brand	NSi
GTIN	00662381062925
Manufacturers Part Number	S12-8V
UPC	662381062925



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

cULus

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	TEDMINIALS
Туре	Vinyl Insulated Spade Terminal
Availability	
minimum qty	50
Packaging	
Carton	1
Package	50
Weight Per each	0.204
Uses, Certifications, and Standards	
Application	Wire Termination
environmental conditions	75 C