



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



S166N 16-14 Nylon Spade # 6 Stud

Nsi Industries

| | |
|------------------|---|
| Catalog Number | S166N |
| Manufacturer | Nsi Industries |
| Description | 16-14 Awg Nylon Insulated Spade #6 Stud, 100 Per Pack |
| Weight per unit | 0.2700 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|---------------------|------------------|
| Material | Nylon Insulation |
| Number of Terminals | 1 |
| Terminal Size | # 6 |
| Voltage Rating | 600 V |
| Wire Size | 16-14 AWG |

Material, Color, and Finish

| | |
|-------|------|
| Color | Blue |
|-------|------|

Descriptions

| | |
|------------------------|---|
| Description | 16-14 NYLON SPADE # 6 STUD |
| extra long description | NSI S16-6N 16-14 Vinyl Flange Spade |
| Features | 16-14 AWG Nylon Insulated Spade #6 Stud, 100 Per Pack |
| Long Description | 16-14 AWG Nylon Insulated Spade #6 Stud, 100 Per Pack |
| Product Type | 16-14 Vinyl Flange Spade 100 Pack # 6 ST |
| Special Features | Nylon Insulated Spade Terminal 16-14 AWG - 100 Pack |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00662381063267 |
| Manufacturers Part Number | S16-6N |
| UPC | 662381063267 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------------------|
| Category Description | TERMINALS |
| Type | Nylon Insulated Spade Terminal |

Availability

| | |
|-------------|-----|
| minimum qty | 100 |
|-------------|-----|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 100 |
| Weight Per each | 0.27 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

| | |
|--------------------------------|------------------------|
| Application | Wire Termination |
| environmental conditions | 105 C |
| standard | cULus |