



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



S226VL 22-18 Vinyl LCK Spade #6stud

Nsi Industries

| | |
|------------------|---|
| Catalog Number | S226VL |
| Manufacturer | Nsi Industries |
| Description | 22-18 Awg, # 6 Stud Vinyl Insulated Locking Spade, 100 Per Pack |
| Weight per unit | 0.1600 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|---------------------|------------------|
| Material | Vinyl Insulation |
| Number of Terminals | 1 |
| Terminal Size | # 6 |
| Voltage Rating | 300 V |
| Wire Size | 22-18 AWG |

Material, Color, and Finish

| | |
|-------|-----|
| Color | Red |
|-------|-----|

Descriptions

| | |
|------------------------|---|
| Description | 22-18 VINYL LCK SPADE #6STUD |
| extra long description | NSI S22-6V-L 22-18 Nylon Locking Sp |
| Features | 22-18 AWG, # 6 Stud Vinyl Insulated Locking Spade, 100 Per Pack |
| Long Description | 22-18 AWG, # 6 Stud Vinyl Insulated Locking Spade, 100 Per Pack |
| Product Type | 22-18 Nylon Locking Spade, 100 Per Pack |
| Special Features | Vinyl Insulated Locking Spade Terminal 22-18 AWG - 100 Pack |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00662381062659 |
| Manufacturers Part Number | S22-6V-L |
| UPC | 662381062659 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | TERMINALS |
| Type | Vinyl Insulated Locking Spade Terminal |

Availability

| | |
|-------------|-----|
| minimum qty | 100 |
|-------------|-----|

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 100 |
| Weight Per each | 0.16 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

| | |
|--------------------------------|------------------------|
| Application | Wire Termination |
| environmental conditions | 75 C |
| standard | cULus |