



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Fast-Acting, High-Breaking Capacity Fuse

**S501-2-R**

**UPC:**051712648875

### Dimensions:

- **Height:** .787 IN
- **Length:** .787 IN
- **Width:** .197 IN

**Weight:**.001 LB

### Warranties:

- Not Applicable

### Specifications:

- **Type:** Small dimension, European (IEC)
- **Application:** Electronic circuits
- **Amperage Rating:** 2A
- **Voltage Rating:** 250 Vac or less, 32 Vdc (self certified)
- **Interrupt Rating:** 1.5 kAIC at 250 Vac
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Voltage Drop:** Typical: 205 mV
- **Material:** Ceramic tube, Silver-plated brass endcaps
- **Frequency Rating:** 50 Hz
- **Connection:** Ferrule end X ferrule end

### Supporting documents:

- [S501 2A BUSS FUSE](#)

**Certifications:** No Data

### Product compliance:

- CE Marked
- VDE
- CCC Marked
- RoHS Compliant







Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Fast-Acting, High-Breaking Capacity Fuse

**S501-2-R**

**UPC:**051712648875

### Dimensions:

- **Height:** .787 IN
- **Length:** .787 IN
- **Width:** .197 IN

**Weight:**.001 LB

### Warranties:

- Not Applicable

### Specifications:

- **Type:** Small dimension, European (IEC)
- **Application:** Electronic circuits
- **Amperage Rating:** 2A
- **Voltage Rating:** 250 Vac or less, 32 Vdc (self certified)
- **Interrupt Rating:** 1.5 kAIC at 250 Vac
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Voltage Drop:** Typical: 205 mV
- **Material:** Ceramic tube, Silver-plated brass endcaps
- **Frequency Rating:** 50 Hz
- **Connection:** Ferrule end X ferrule end

### Supporting documents:

- [S501 2A BUSS FUSE](#)

**Certifications:** No Data

### Product compliance:

- CE Marked
- VDE
- CCC Marked
- RoHS Compliant



